EasyBraid Co. EBM8LR403 Datasheet **Technical Specifications** EBM8LR403 Long Reach Chisel 60° 1.78mm (0.07") 15.0mm (0.59") Tip Style: Long Reach Chisel 60° .78mm (0.07") Tip Width: 1.78mm (0.07") Tip Length: 15.00mm (0.59") 800°F Type Cartridge¹: 420°C - 475°C RoHS Compliant² / Lead Free: YES Equivalent to: STTC-842 For Use With: EB-9000S **Material Composition** Stainless Steel Shaft Lead-Free Tip Gold Plated Connector Chromium All components are RoHS **RoHS** Iron Plating compliant and Lead-Free. Copper Core Solder ¹ Easybraid tip cartridges will typically idle within a temperature range of +/-1.1°C. However, there is variation in idle temperature across tip geometries within an individual temperature series. Easybraid offers a wide variety of tip geometries from 0.4mm fine point tip to 5m chisel. The length and geometry of a tip will have an influence on the tip idle temperature. To accurately measure idle temperature it will depend greatly on the measurement method, technique and

equipment used. Two different methods or the use of alternative equipment will produce different test results.

² Please refer to <u>http://www.rohs.gov.uk</u> for details on RoHS Compliance.

Copyright © 2010 Easybraid Co. All Rights Reserved