

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C	STORAGE TEMPERATURE RANGE	-55 °C TO 85 °C
	VOLTAGE	—	OPERATING HUMIDITY RANGE	— % TO — %
	CURRENT	—	APPLICABLE CABLE	—

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	×	×
MARKING	CONFIRMED VISUALLY.		×	×


ENVIRONMENTAL CHARACTERISTICS

RAPID CHANGE OF TEMPERATURE	TEMPERATURE -40 → 5~35 → 105 → 5~35 °C TIME 30 → 2~3 → 30 → 2~3 min UNDER 10 CYCLES.	NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	×	—
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	NO HEAVY CORROSION.	×	—

REMARKS	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	<i>F. Soniguchi</i> 06.02.06	<i>F. Soniguchi</i> 06.02.06	<i>Y. Enami</i> 06.02.07	<i>H. Miwa</i> 06.02.08	

Unless otherwise specified, refer to JIS C 5402.

Note QT:Qualification Test AT:Assurance Test O:Applicable Test

 HIROSE ELECTRIC CO., LTD.	SPECIFICATION SHEET	PART NO.	FI-20-CV(60)
		CODE NO.(OLD)	DRAWING NO.
CL	ELC4-040857-01		CL230-0501-4-60

1
1

TO
Q