

M12-P-ACC-HOUSING F REAR MOUNTING



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 21 03 302 2000 407 |
| Specification | M12-P-ACC-HOUSING F REAR MOUNTING |
| HARTING eCatalogue | https://b2b.harting.com/21033022000407 |

Identification

| | |
|------------------------------|-------------------------|
| Category | Accessories |
| Series | Circular connectors M12 |
| Type of accessory | Housing |
| Description of the accessory | for rear mounting |

Version

| | |
|--------------|---------------|
| Gender | Female |
| Locking type | Screw locking |

Technical characteristics

| | |
|--|-----------------------------|
| Tightening torque | 2 Nm Lock nut |
| Degree of protection acc. to IEC 60529 | IP65 / IP67 mated condition |

Material properties

| | |
|--------------------------------------|--|
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| California Proposition 65 substances | Yes |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|----------------------|
| California Proposition 65 substances | Lead |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

| | |
|----------|--|
| UL / CSA | UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079 |
|----------|--|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 30 |
| Net weight | 16 g |
| Country of origin | Romania |
| European customs tariff number | 85389099 |
| GTIN | 5713140236455 |
| eCl@ss | 27440292 Connector component (accessories) |