

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com


TAA-Compliant Protect It! 7-Outlet Surge Protector, 7 ft. (2.13 m) Cord, 2450 Joules, Black Housing

MODEL NUMBER: SUPER7BTAA











Description

Tripp Lite's Super7BTAA is compliant with the Federal Trade Agreement Act (TAA) for GSA schedule purchases. The SUPER7B Surge Suppressor from Tripp Lite has 7 outlets, a 7-ft. (2.13 m) cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 2450 joules to handle the strongest surges. \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- Compliant with the Federal Trade Agreement Act (TAA) for GSA Schedule purchases
- 7 outlets
- 7-ft. (2.13 m) cord with space-saving right-angle plug
- Surge suppression rating: 2450 joules
- Child Safety Covers
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing
 equipment damage and indicating replacement is required
- EMI/RFI noise filtering
- \$75,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only) covers connected equipment
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332183422 |

Highlights

- Compliant with the Federal Trade Agreement Act (TAA) for GSA Schedule purchases
- 7 outlets/7-ft. (2.13 m) cord
- 2450 joule rating

Package Includes

- SUPER7BTAA Surge Suppressor
- Instruction manual with warranty information



| INPUT | | |
|------------------------------------|---|--|
| Nominal Input Voltage(s) Supported | 120V AC | |
| Recommended Electrical Service | 120V (110-125V) | |
| Input Cord Gauge Type | 14 gauge; SJT | |
| Input Cord Gauge (AWG) | 14 | |
| Voltage Compatibility (VAC) | 120 | |
| Maximum Surge Amps | 144000 | |
| Input Plug Type | NEMA 5-15P | |
| Input Cord Details | SJT | |
| Input Cord Length (ft.) | 7 | |
| Right-Angle Plug | Yes | |
| Input Cord Length (m) | 2.13 | |
| Integrated Cord Clip | No | |
| OUTPUT | | |
| Frequency Compatibility | 50 / 60 Hz | |
| Output (Watts) | 1800 | |
| Output Receptacles | (7) 5-15R | |
| Circuit Breaker (amps) | 15 | |
| Transformer Accommodation | (3) Yes | |
| Right-Angle Outlets | No | |
| USER INTERFACE, ALERTS & CONTROLS | | |
| Diagnostic LED(s) | Yes | |
| Switches | Two position on/off power switch | |
| Diagnostic LED Details | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status | |
| SURGE / NOISE SUPPRESSION | | |
| AC Suppression Joule Rating | 2450 | |
| AC Suppression Response Time | < 1 ns | |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression | |
| UL1449 Let Through Rating | 400 L-G, 400 L-N, 400 N-G | |
| EMI / RFI Filtering | Up to 20 dB | |
| Automatic Shut-Off | Yes | |
| DATALINE SURGE SUPPRESSION | | |



| Cable (Coax) Protection | No | |
|---|---|--|
| Network (Ethernet) Protection | No | |
| Telephone/DSL Protection | No | |
| PHYSICAL | | |
| Material of Construction | Plastic | |
| Power Cord Color | Black | |
| Housing Color | Black | |
| Mounting Holes or Slots | Yes | |
| Receptacle Color | Black | |
| Shipping Dimensions (hwd / cm) | 0.00 × 0.00 × 0.00 | |
| Shipping Dimensions (hwd / in.) | 0.00 × 0.00 × 0.00 | |
| Shipping Weight (kg) | 0.00 | |
| Shipping Weight (lbs.) | 0.00 | |
| Unit Dimensions (hwd / in.) | 2.4 x 2.0 x 13.3 | |
| Unit Dimensions (hwd / cm) | 5.1 x 6.2 x 33.7 | |
| Unit Weight (lbs.) | 1.2 | |
| Unit Weight (kg) | 0.54 | |
| FEATURES & SPECIFICATIONS | | |
| Antimicrobial | No | |
| Rotatable Outlets | No | |
| STANDARDS & COMPLIANCE | | |
| Product Certifications | cUL Listed; UL 1363; UL 1449; CAN/CSA-C22.2 No. 269.3 (Canada); CAN/CSA-C22.2 No. 308 (Canada) | |
| WARRANTY | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$75,000 Ultimate Lifetime Insurance | |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies