E43002

Г

Welding adapter for level sensors

WELDING ADAPTER 50/D16



| <i>№</i> 30 <i>№</i> 16,3 Ø50 | | |
|-------------------------------------|-------|--|
| Application | | |
| Design | | for capacitive level sensors LK, LI, LT, LL |
| Installation | | Clamp fitting |
| Pressure rating | [bar] | 0.5 |
| Operating conditions | | |
| Ambient temperature | [°C] | 080 |
| Tests / approvals | | |
| Pressure Equipment Directive | | A possible classification to PED depends on the application and has to be carried out by the user / operator. |
| Pressure Equipment Directive EAC | | The adapter is intended for use in devices, machines and installations that do not fall under the categories of the technical rule TR CU 032/2013. |
| Safety instructions | | The compatibility between medium and product material has to be checked in all applications. |
| Mechanical data | | |
| Weight | [g] | 394.5 |
| Dimensions | [mm] | Ø 50 / L = 37.5 |
| Materials | | flange: stainless steel; Lock nut: stainless steel; spacer: brass; clamping ring: FKM |
| Tightening torque | [Nm] | 69 |
| Sensor connection | | Ø 16 mm |
| Process connection | | welding adapter Ø 50 mm |
| Remarks | | |
| Pack quantity | | 1 pcs. |
| | | |