




## Screw Terminal Blocks

### 1000/12 DS

terminal block, 12 pole, insulating material: PA, cross-section rating: 6.0 mm<sup>2</sup>, pin spacing: 12.00 mm, mounting hole diameter: 3.6 mm, wire protector (DS): yes, fixing: screw, voltage rating: 500 V, current rating: 41 A



### Order Info

<b>reference number (ref.no.)</b>	125312
<b>PU</b>	25
<b>EAN</b>	4028012100309

### Type

<b>type</b>	terminal block
<b>number of poles</b>	12 pole
<b>clamping units per pole</b>	1
<b>colour</b>	natural
<b>cross-section rating</b>	6.0 mm <sup>2</sup>
<b>connection type</b>	screw
<b>wire protector (DS)</b>	yes

### Technical Data

<b>voltage rating</b>	500 V
<b>current rating</b>	41 A
<b>insulating material</b>	PA
<b>contact material</b>	brass
<b>core cross-section min.</b>	0.5 mm <sup>2</sup>
<b>core cross-section max.</b>	6.0 mm <sup>2</sup>
<b>flammability rating</b>	V-2
<b>min. ambient temperature</b>	-40 °C
<b>max. ambient temperature operation</b>	85 °C
<b>type of conductor solid</b>	yes
<b>type of conductor flexible</b>	yes
<b>type of conductor stranded</b>	yes
<b>stripping length</b>	7.5-8.0 mm
<b>assembly contact screw</b>	0,8x4,0 / ⚙ 0,8 Nm
<b>mounting hole diameter</b>	3.6 mm
<b>pin spacing</b>	12.00 mm
<b>fixing</b>	screw

## Approvals

<b>acc. to EN 60998</b>	<a href="#">Download PDF</a>
<b>acc. to UL</b>	<a href="#">Download PDF</a>
<b>acc. to CSA</b>	<a href="#">Download PDF</a>

## Accessories

<b>1000 BZ/12</b>	191412
<b>ABK 406/12</b>	193312
<b>ZEL 110</b>	196420