




## LVO-MCL-13-AN

Ruland LVO-MCL-13-AN, 13mm One-Piece Shaft Collar with Clamping Lever, Anodized Aluminum Collar with Zinc Plated Lever, 30mm OD, 11mm Width





## Description

Ruland LVO-MCL-13-AN is a one-piece quick clamping shaft collar with clamping lever with a 13mm bore, 30mm OD, and 11mm width. It is made from MCL-13-AN and LF30-CL-M4:12-ZS. The clamp style design does not mar the shaft, is easy to remove, and is indefinitely adjustable. The threaded stud on the lever is used in place of standard collar hardware. When combined, the two parts create a shaft collar that requires no tools to install, remove, or reposition and is ideally suited for packaging, printing, and other applications where frequent setup changes and adjustments are needed. Once the lever is installed in the shaft collar, users simply turn the lever until they meet their desired torque. The adjustable lever can be reposition by the user without the loss of holding power by lifting the handle and twisting it 40° to lock it in a new position. This allows for use in space constrained environments where 360° rotation is not possible to fully seat the lever. MCL-13-AN is made from high-strenth 2024 aluminum with a black anodized finish. LF30-CL-M4:12-ZS has a zinc plated steel handle and stainless steel threaded stud. This material combination allows for a lightweight durable quick clamping and release component that is suitable for most industrial applications and has higher corrosion resistance properties than types with no anodize. The lever is orange for safety and ease of identification. MCL-13-AN is manufactured by Ruland and LF30-CL-M4:12-ZS is manufactured by Otto Ganter. LVO-MCL-13-AN is RoHS3 and REACH compliant.

## **Product Specifications**

Bore (B)13 mmBore Tolerance+0.050 mm / +0.012 mmOuter Diameter (OD)30 mmCenter to Lever Top H132.2 mmWidth (W)13 mmWidth Tolerance+0.076 mm / -0.254 mmLever Length L130 mmLever Height H232 mmHub Diameter DH13 mmSleeve Length L212 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM4Hex Wrench Size3.0 mmSeating Torque2.5 NmScrew Location (R)11.00 mmNumber of Screws1 eaCollar Part NumberMCL-13-ANLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrageHandle Material303 Stainless SteelManufacturerRuland ManufacturingShaft Collar - USA Lever - GermanyShaft Collar - USA Lever - GermanyWeight (Ibs)0.098400UPC634529292945Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine subility for a particular applicatProp 65MWARNING This product can expose you to the chemical Soots, Benzene, Lead, Nickel (metallic), k	r roduct opcomoations			
Width (W)13 mmWidth Tolerance+0.076 mm / -0.254 mmLever Length L130 mmLever Height H232 mmHub Diameter DH13 mmSleeve Length L212 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM4Hex Wrench Size3.0 mmSeating Torque2.5 NmScrew Location (R)11.00 mmNumber of Screws1 eaCollar Part NumberMCL-13-ANLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.098400UPC634529292945Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicat	Bore (B)	13 mm	Bore Tolerance	+0.050 mm / +0.012 mm
Lever Length L130 mmLever Height H232 mmHub Diameter DH13 mmSleeve Length L212 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM4Hex Wrench Size3.0 mmSeating Torque2.5 NmScrew Location (R)11.00 mmNumber of Screws1 eaCollar Part NumberMCL-13-ANLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.098400UPC634529292945Mote 1Performance ratings are for guidance only. The user must determine suitability for a particular applicat	Outer Diameter (OD)	30 mm	Center to Lever Top H1	32.2 mm
Hub Diameter DH13 mmSleeve Length L212 mmRecommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM4Hex Wrench Size3.0 mmSeating Torque2.5 NmScrew Location (R)11.00 mmNumber of Screws1 eaCollar Part NumberMCL-13-ANLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (lbs)0.098400UPC634529292945Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicat	Width (W)	13 mm	Width Tolerance	+0.076 mm / -0.254 mm
Recommended Shaft Tolerance+0.000 mm / -0.013 mmThread THM4Hex Wrench Size3.0 mmSeating Torque2.5 NmScrew Location (R)11.00 mmNumber of Screws1 eaCollar Part NumberMCL-13-ANLever Part NumberLF30-CL-M4:12-ZS-QCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.098400UPC634529292945Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicat	Lever Length L1	30 mm	Lever Height H2	32 mm
Hex Wrench Size3.0 mmSeating Torque2.5 NmScrew Location (R)11.00 mmNumber of Screws1 eaCollar Part NumberMCL-13-ANLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.098400UPC634529292945Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitbility for a particular applicat	Hub Diameter DH	13 mm	Sleeve Length L2	12 mm
Screw Location (R)11.00 mmNumber of Screws1 eaCollar Part NumberMCL-13-ANLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.098400UPC634529292945Note 1Performance ratings are for guidance only. The user must determine suitability for a particular applicat	Recommended Shaft Tolerance	+0.000 mm / -0.013 mm	Thread TH	M4
Collar Part NumberMCL-13-ANLever Part NumberLF30-CL-M4:12-ZS-OCollar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.098400UPC634529292945Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitbility for a particular applicat	Hex Wrench Size	3.0 mm	Seating Torque	2.5 Nm
Collar MaterialAluminumCollar FinishBlack AnodizedHandle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.098400UPC634529292945Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine sublity for a particular application	Screw Location (R)	11.00 mm	Number of Screws	1 ea
Handle ColorOrangeHandle MaterialZincHandle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.098400UPC634529292945Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine sublity for a particular application	Collar Part Number	MCL-13-AN	Lever Part Number	LF30-CL-M4:12-ZS-O
Handle FinishPowder CoatedInsert and Screw Material303 Stainless SteelManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.098400UPC634529292945Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Collar Material	Aluminum	Collar Finish	Black Anodized
ManufacturerRuland ManufacturingCountry of OriginShaft Collar - USA Lever - GermanyWeight (Ibs)0.098400UPC634529292945Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Handle Color	Orange	Handle Material	Zinc
Lever - Germany   Weight (lbs) 0.098400 UPC 634529292945   Tariff Code 8483.60.8000 UNSPC 31162811   Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application	Handle Finish	Powder Coated	Insert and Screw Material	303 Stainless Steel
Weight (lbs)0.098400UPC634529292945Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application	Manufacturer	Ruland Manufacturing	Country of Origin	Shaft Collar - USA
Tariff Code8483.60.8000UNSPC31162811Note 1Performance ratings are for guidance only. The user must determine suitability for a particular application				Lever - Germany
Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application	Weight (Ibs)	0.098400	UPC	634529292945
	Tariff Code	8483.60.8000	UNSPC	31162811
Prop 65	Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
	Prop 65	AWARNING This product can exp	oose you to the chemical Soots, Ben	zene, Lead, Nickel (metallic), knowr

to the State of California to cause cancer