

May.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
Rating	Operating Temperature Range	-°C to -°C	Storage Temperature Range	-°C to -°C	
	Voltage	-	Current		
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
General Examination	Examined visually and with a measuring instrument.		According to drawing.	X	-
Marking	Confirmed visually.		According to drawing.	X	-
Supplement : Fluke Networks will guarantee and maintain the product functions of this product. Please contact Fluke Networks for inquiries regarding this product.					
△	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
0	0				
Note			APPROVED	MN.KENJO	20190515
			CHECKED	KI.NAGANUMA	20190515
			DESIGNED	JY.IGA	20190515
			DRAWN	JY.IGA	20190515
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC-388328-00-00	
HRS	SPECIFICATION SHEET		PART NO.	DSX-CHA-5-IX-S	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL251-1001-0-00	△ 1/1