



Tapmatic® Edge Lube

Cutting Fluid



FEATURES

- Low toxic, biodegradable, low odor
- Extends grinding wheel life
- Does not contain any hazardous chemicals
- Eliminates heat build-up and belt loading
- Excellent for belt, wheel or disc grinding, and sawing applications
- Biodegradable, solid, white, waxy bar
- Recognized by the USDA BioPreferred™ program
- Water rinsable
- Safe on all metals

APPLICATIONS

- Boring
- Broaching
- Drilling
- Engraving
- Grinding
- Tapping
- Threading
- Turning

PROPERTIES

Appearance / Physical State	Solid
Odor	Oily
Melting / Freezing Point	Not established
Boiling Point / Range	Not established
Vapor Pressure	Not established
Partition Coefficient	> 1
Percent volatile	0%
Flammability	Not available.
Propellant	N/A
VOC Content	0% per U.S. State and Federal Consumer Product Regulations
Color	Off-white
Flash Point	338.0°F (170.0°C) Tag Closed Cup
Density	Not available
Evaporation Rate	None
Vapor density	Not established
Auto-Ignition Temperature	Not established
Viscosity	Not established
Specific Gravity	0.82 - 0.84 @ 20°C
Temperature Range	Not established
4-Ball Weld Load	Not established

DIRECTIONS

Hold against rotating or stationary cutting tools, grinding wheels or belts. Recap when not in use, keep in cool place.

HANDLING

Observe good industrial hygiene practices

STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
43200	C43200	13 wt oz / 364 g	bar	10	10 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved