



- Material
- ② Item ③ Clamp: Brass(CuZn) Ni plated
 - Item ④ Terminal screw :Steel Zinc plating"- "slot type
 - Item ⑤ Female contact: PhBz, Tin plated
 - Item ⑥ Terminal(housing): Thermoplastic (UL94V-0) Green(RAL6018/T)
 - Item ⑦ Terminal(cover): Thermoplastic (UL94V-0) Green(RAL6018/T)

Electrical cULus/VDE
 Voltage rating: 300VAC/300VAC
 Current rating: 10A/10.5A
 Wire range: 1.5mm²
 Solid wire(AWG): 16-28/16-28
 Stranded wire(AWG): 16-28/16-28
 Torque: 3lb·In /0.2N.m
 Screw: M2
 Wire strip length: 6-7 mm
 Withstanding Voltage: 1.6kV/2.5kV
 Operating temperature: -40°C to +115°C
 Safety Approval:

② Dimension

DIM A	Nx3.81
DIM B	(N-1)x3.81

N=Number of poles

Poles	Tolerance DIM A	Tolerance DIM B
2P-6P	±0.15	±0.15
7P-12P	±0.20	±0.20
13P-18P	±0.25	±0.25
19P-24P	±0.30	±0.30

RoHS compliant
 Unit: mm

 File No.: E349947

Scale	Free	Id.	Modification	Date	Name
TOLERANCE					
X.	±0.50			10.12.2009	Dean
X.X	±0.30				
X.XX	±0.10	③	Add UL	18.04.2016	Amy
DIM	TOL	②	Update	06.03.2013	Amy
X.°	±1°	①	Drawn	10.12.2009	Dean
Angle	TOL				

ASSMANN
 wsw components

Customer-No.
 ASSMANN WSW-No.
 A-TB381-TJXXU
 Drawing-No.
 ASS 3832 CO
 rev03

Replace

Sheet