



NEMA 5-15R  
MOLDED CONNECTOR  
COLOR: BLACK

**TECHNICAL:**  
LISTED: cULus  
RATED SUPPLY VOLTAGE: 120 VAC  
RATED CURRENT: UP TO 15 AMPS OR CABLE RATING  
RESET TYPE: AUTOMATIC OR MANUAL  
OPERATING FREQUENCY: 60 Hz  
TYPE: CLASS A  
GROUND TRIP CURRENT: 4-6 mA  
OVERLOAD CURRENT: 90 AMP 125 VAC  
INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE  
ENDURANCE OPERATIONS: 3000 OPERATIONS

MATERIAL NO.	ENGINEERING NO.	LENGTH "L"	POWER-UP
1301530091	15054-1A	2 FT ± 1 IN	AUTO
1301530095	15054-25A	25 FT ± 2 IN	AUTO
1301530092	15054-1M	2 FT ± 1 IN	MANUAL
1301530096	15054-25M	25 FT ± 2 IN	MANUAL

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
FUNCTIONAL SYMBOLS		DIMENSION UNITS		SCALE		CURRENT REV DESC: MIGRATION TO ECTR/NX					
= 0		INCH		NTS		<p><b>molex</b></p> <p>120V 15A GFCI PLUG W/ MOLDED CONNECTOR NEMA 5-15</p> <p>PRODUCT CUSTOMER DRAWING</p> <p>DOCUMENT NUMBER: SD-130153-017   DOC TYPE: PSD   DOC PART: 001   REVISION: A1</p>					
= 0		GENERAL TOLERANCES (UNLESS SPECIFIED)									
= 0		ANGULAR TOL ± 0.5°									
DIVISIONAL SYMBOLS		3 PLACES ±									
		2 PLACES ± 0.13									
		1 PLACE ± 0.25									
		0 PLACES ±				EC NO: 684571		DRWN: V BASUTHKARP		2021/11/06	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES	
		B-SIZE		130153		MATERIAL NUMBER		CUSTOMER			
		SEE TABLE		GENERAL MARKET		SHEET NUMBER		1 OF 1			