



ELECTRICAL SPECIFICATIONS

| | |
|-----------------------------|------------------|
| FREQUENCY RANGE | 5650 TO 7150 MHz |
| RETURN LOSS | -19 dB MAX |
| INSERTION LOSS | 0.5 dB MAX |
| ISOLATION | -18 dB MAX |
| IMD3 (dBc) @ +33 dBm POUT | -65 dBc MAX |
| FORWARD POWER | 20 W MAX |
| REVERSE POWER | 10 W MAX |
| OPERATING TEMPERATURE RANGE | -40 TO +85 °C |
| STORAGE TEMPERATURE RANGE | -45 TO +85 °C |
| DIRECTION | CW |

MATERIAL SPECIFICATIONS :

BODY MATERIAL : STEEL, SILVER PLATED
PIN : COPPER, GOLD PLATED

NOTES :

- 1.STANDARD INPUT/OUTPUT IMPEDANCE 50 Ohm.
- 2.LEAD FREE, NO Nd MATERIAL, BeO FREE.
- 3.THE DIMENSION OF DATA MATRIX IS 3.0X3.0MM INFORMATION INCLUDING WORK ORDER NUMBER-SERIAL NUMBER-MATERIAL NUMBER
- 4.THIS PART COMPLIES WITH ALL RoHS REQUIREMENTS

ENG PART#: 801-565-715-PT040

| | | | | | | | | | |
|---|--|--------------|--------------------------------------|--|---------|------------|-----------------|----------|--------------|
| THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | | | | | | | |
| FUNCTIONAL SYMBOLS | DIMENSION UNITS | SCALE | CURRENT REV DESC: | | | | | | |
| $F_A=0$ | MM | 1:1 | RELEASE TO PROD | | | | | | |
| $F_P=0$ | GENERAL TOLERANCES (UNLESS SPECIFIED) | | EC NO: 696580 | | | | | | |
| $F_D=0$ | mm INCH | | DRWN: SREN05 2022/02/21 | | | | | | |
| DIVISIONAL SYMBOLS | 4 PLACES | ±0.005 ±---- | CHK'D: JLI252 2022/02/23 | | | | | | |
| | 3 PLACES | ±0.025 ±---- | APPR: HWANG186 2022/03/01 | | | | | | |
| | 2 PLACES | ±0.13 ±---- | INITIAL REVISION: | | | | | | |
| | 1 PLACE | ±0.25 ±---- | DRWN: SREN05 2021/12/08 | | | | | | |
| | 0 PLACES | ±0.4 ±---- | APPR: HWANG186 2022/03/01 | | | | | | |
| | ANGULAR TOL ± 1.5 ° | | DOCUMENT NUMBER | | | | | | |
| | DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | THIRD ANGLE PROJECTION | | DRAWING | SERIES | MATERIAL NUMBER | CUSTOMER | SHEET NUMBER |
| | | | A3-SIZE | | 73591 | 0735912081 | CUSTOM PART | 1 OF 1 | |
| | | | 735912081 PSD 000 A | | | | | | |
| | | | RESTRICTED PRODUCT CUSTOMER DRAWING | | | | | | |
| | | | SMT ISOLATOR/5.65 GHZ TO 7.15 GHZ/CW | | | | | | |
| | | | molex | | | | | | |