




USSK28-20MM-20MM-F

Ruland USSK28-20MM-20MM-F, 20mm x 20mm Single Universal Joint, Friction Bearing, Steel, Set Screw With Keyway, 44.3mm OD, 127.0mm Length





Description

Ruland USSK28-20MM-20MM-F is a single cardan friction bearing universal joint with 20mm x 20mm bores, 6mm x 6mm keyways, 44.3mm OD, 127.0mm length, and 5/16-18 set screws. It is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. USSK28-20MM-20MM-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT28/44-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

20 mm	Small Bore (B2)	20 mm
6 mm	Keyway (K2)	6 mm
40.9 mm	B2 Max Shaft Penetration	40.9 mm
44.3 mm	Bore Tolerance	+0.025 mm / -0.000 mm
127.0 mm	Yoke Length (LY)	63.5 mm
40.9 mm	Broached Set Screw	5/16-18
Black Oxide	Peak Torque	1638.3 Nm
327.7 Nm	Max Operating Angle	45°
Alloy Steel	Manufacturer	Belden Universal
USA	Recommended Lubricant	LUBRIPLATE No. 1200-2
UBOOT28/44-NI-KIT	UPC	63452932427
8483.60.4000	UNSPC	25173810
Performance ratings are for guidance only. The user must determine suitability for a particular application.		
▲WARNING This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov .		
	6 mm 40.9 mm 44.3 mm 127.0 mm 40.9 mm Black Oxide 327.7 Nm Alloy Steel USA UBOOT28/44-NI-KIT 8483.60.4000 Performance ratings are for gui	6 mm Keyway (K2) 40.9 mm B2 Max Shaft Penetration 44.3 mm Bore Tolerance 127.0 mm Yoke Length (LY) 40.9 mm Broached Set Screw Black Oxide Peak Torque 327.7 Nm Max Operating Angle Alloy Steel Manufacturer USA Recommended Lubricant UBOOT28/44-NI-KIT UPC 8483.60.4000 UNSPC Performance ratings are for guidance only. The user must determine California to cause cancer and birth defects or other reproductive has