

Readability **0.01 kg – 0.02 lb / 0.02 kg – 0.05 lb / 0.05 kg – 0.1 lb**



► Features

- RS232 interface.
- Full Range tare function.
- Auto shut-off.
- Removable display

► Standard Functions

- Weighing.
- Hold Function.

► Accesories Included

- Power adapter.
- Wall mount.

► TECHNICAL DATA

	VE-BFS30	VE-BFS60	VE-BFS100
Model			
Capacity	30 kg / 66 lb	60 kg / 130 lb	100 kg / 220 lb
Readability	0.01 kg / 0.02 lb	0.02 kg / 0.05 lb	0.05 kg / 0.1 lb
Repeatability	±0.01 kg / 0.02 lb	±0.02 kg / 0.05 lb	±0.05 kg / 0.1 lb
Linearity	±0.02 kg / 0.04 lb	±0.04 kg / 0.1 lb	±0.1 kg / 0.2 lb
Weighing Units	kg, lb, oz		
Calibration	External		
Pan Size	310 x 300mm / 12.2" x 11.8"		
Stabilization Time	2 seconds		
Interface	RS232		
Display	LCD, digit height 15mm / 0.6"		
Housing	Metal housing and stainless steel pan		
Operating Environment	5° to 40°C / 41° to 104°F		
Overall Dimensions	315 x 325 x 55 mm / 12.4" x 12.7" x 2.2"		
Power Supply	110/240V, 50/60 Hz AC Adapter and 6MAA batteries (not included)		
Net Weight	5.5 kg / 12 lb		
Warranty	1 year		