



Interface-Relay-Compact (IRC) socket base IRC with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 6, 12 or 24 VAC/DC

Business data	
Article number	<u>16193.2</u>
Article name	IRCP 6-12-24V AC/DC
GTIN (EAN)	4044211187293
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	35.4 g
Weight per piece (including packaging)	35.4 g
Unit of weight	G
Customs number	85369010
Country of origin	IT
Product description	Relay socket base with screw connection



Technical data

Dimensions	
Length	94.3 mm
Width	6.2 mm
Height TS 35 / 7.5 with BA	90.7 mm
Ratings	
Rated voltage Un	6-12-24 VAC/DC -
Overvoltage category	III
Contamination degree	3
Connection data	
Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm ²
Wire cross-section single-core (rigid), max.	2.5 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Stripping length	10 mm
Torque	0.5 Nm
Output data	
Switching voltage / switching voltage max.	250 / 400 VAC
Contact configuration	1 CO contact
Materials	
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	70 °C
Further technical data	
Degree of protection	IP20
Status display	\checkmark
Can hold a fuse in the P-contact	\checkmark
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes



Approvals

Standards and regulations			
CE compliant	yes		
cUL approval	CSA-C22.2 No. 14		
UL approval	UL 508		
UL Recognized	1		
cUL Recognized	1		



Media





Accessories

Cross-connector					
	External cross-connector insulated for Interface-Relay-Compact (IRC), 16-pole, can be shortened, Voltage: 250 V, Current: 6 A				
	Article number	Article name	GTIN (EAN)	Packaging unit	
	16209.4	AQI/IRC/16 BK	4044211187651	10	
Quick marking					
	Terminal marker, Length: 12 mm, Width: 6 mm, Colour: White				
	Article number Article name GTIN (EAN)				
	28262.7	PC-CPM-11 E 6X12/48 WH	4044211211790	1344	
	Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White				
	Article number	Article name	GTIN (EAN)	Packaging unit	
	3884.7	MC GS 6x12 R WH	4044211154547	600 ST	
	Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White				
	Article number	Article name	GTIN (EAN)	Packaging unit	

Screwdriver

Screwdriver with bare blade, Colour: Black-grey

- Connecte .	Article number	Article name	GTIN (EAN)	Packaging unit
	1086.0	SDB 0,6x3,5	4044211014797	1 ST

Relays



34.51	Plug-in miniature power relay, With multi-layer gold contact, 1 CO contact, Input voltage: 12 VDC				
34.51,7.024.0010 € 5 = 3 U186 42.0010 € 4 = 3 ⊕24V== 6A 250V~U	Article number	Article name	GTIN (EAN)	Packaging unit	
	15558.2	PRC 1/12V DC Au	4044211118389	10 ST	
34 51	Plug-in miniatu 24 VDC	ure power relay, With multi-layer gol	d contact, 1 CO contac	t, Input voltage:	
34.51.7.024.0010 (2000年間) 11日日 40010 (2000年間) 中24V〒6A 250Vへし	Article number	Article name	GTIN (EAN)	Packaging unit	
	15559.2	PRC 1/24V DC Au	4044211118396	10 ST	
	Plug-in miniat	Plug-in miniature power relay, With power contact, 1 CO contact, Input voltage: 5 VDC			
34.51.7.024.0010 (日本) 118日 中24V〒 6A 250V~し	Article number	Article name	GTIN (EAN)	Packaging unit	
	15500.2	PRC 1/5V DC	4044211118174	10 ST	
	Plug-in miniat	Plug-in miniature power relay, With power contact, 1 CO contact, Input voltage: 12 VDC			
34.517.024.0010 金融 UIBB 4.0010 金融 中24V〒 6A 250V し	Article number	Article name	GTIN (EAN)	Packaging unit	
	15501.2	PRC 1/12V DC	4044211118136	10 ST	
	Plug-in miniature power relay, With power contact, 1 CO contact, Input voltage: 24 VDC				
34.51.7.024.0010 (別しまご) U188 4.0010 (金) ま 中24V= 6A 250V~し)	Article number	Article name	GTIN (EAN)	Packaging unit	
	15502.2	PRC 1/24V DC	4044211118143	10 ST	
34.51.7 cm	Plug-in miniatu 5 VDC	Plug-in miniature power relay, With multi-layer gold contact, 1 CO contact, Input voltage: 5 VDC			
34.51.7.024.0010 金、 音音 UI語 40010 金、 音音 中24V - 6A 250V へい	Article number	Article name	GTIN (EAN)	Packaging unit	
	15557.2	PRC 1/5V DC Au	4044211118372	10 ST	

Adapter





Plug adapter for Interface-Relay-Compact (IRC), ribbon plug-in connector, 14-poles, according to IEC 60603-13, for 8 relay channels, Positive switching, Rated voltage: 24 VDC

Article num	ber Article name	GTIN (EAN)	Packaging unit
16229.2	FCA/IRC	4044211187682	10 ST

Partition plate



Partition plate for Interface-Relay-Compact (IRC) for separating relay blocks, variable width: 1.5 or 6.2 mm

Article number	Article name	GTIN (EAN)	Packaging unit
16228.2	TW/IRC	4044211187675	10 ST