Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



RVUCOEW-B50 Connectors - REVConnect Cores 50 Pack

For more Information please call

1-800-Belden1

General Description:

REVConnect Core Pack, Bulk Pack of 50

Usage (Overall)

Suitable Applications: Terminate REVConnect Jacks and Plugs

Physical Characteristics (Overall)

AWG of Cable:	22 to 24, Solid and Stranded Conductors, UTP and Screened Cables		
Body Attachment Method:	Compression		
Contact Attachment Method:	Insulation Piercing		
Contact Plating:	Gold over Nickel		
Tool Requirements:	REVConnect Termination Tool (p/n RVUTT01)		

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

Safety Listing: c(UL)us Listed

Notes (Overall)

Notes: PACKAGING: Bulk 50x core cable managers and caps packaged in a resealable plastic bags WEIGHT: 0.18 lbs

Connectors

Connector Materials:	PBT UL94V-0		
Connector Interface:	RevConnect UTP and Shielded, CAT5E, CAT6+, 10GX		
Current Rating:	1.5 Amps per conductor @ 25°C		
Storage Temperature Range:	-40°C To +70°C		
Installation Temperature Range:	-10°C To +60°C		
Operating Temperature Range:	-10°C To +60°C		

Notes:

Cable Range

- Min: 24 AWG Max: Cable 22 AWG Solid and Stranded
- Insulation Dia. Min: .035 in. (.89 mm) Max: .053 in. (1.34 mm)
- Shielded: Outer Jacket Dia. Min: .235 in. (5.9 mm) Max: .366 in. (9.3 mm)
- Unshielded: Outer Jacket Dia. Max: .366 in. (9.3 mm)

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
RVUCOEW-B50	50 EA	9.500 LB		Q	REVConn Core Pack,

Notes:

Q = STANDARD PACKAGES CANNOT BE BROKEN.

Revision Number: 0 Revision Date: 10-28-2019

© 2020 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

Page 1 of 2 10-28-2020

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



RVUCOEW-B50 Connectors - REVConnect Cores 50 Pack

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Page 2 of 2 10-28-2020