## Data sheet

**SIEMENS** 



Protective film 7; front Type 5, glues over the full area reflection shield matte Further information, quantity and content: See technical data

6AV6881-0GJ22-0AA0

General information		
Product type designation	Protective film 7" front, surface, type 5	
Installation type/mounting		
Mounting in portrait format possible	Yes	
Mounting in landscape format possible	Yes	
Standards, approvals, certificates		
CE mark	No; No CE marking obligation	
EAC (formerly Gost-R)	Yes	
RoHS conformity	Yes; unnecessary	
Ambient conditions		
Suited for indoor use	Yes; Processing temperature 5 °C to 32 °C, empirical value	
Suited for outdoor use	No; possible under certain conditions	
Ambient temperature during operation		
• min.	-20 °C	
• max.	80 °C	
Ambient temperature during storage/transportation		
• min.	15 °C	
• max.	30 °C	
Relative humidity		
Operation, max.	50 %	
Mechanics/material		
Material	Polyester with functional hard layer, dirt-repellant, URM55, silicone adhesive layer	
• Plastic	Yes; Non-reflecting, matte, can be removed without residue, hard-coated, dirt-repellant	
• PET	Yes; Non-antistatic, non-reflecting, scratch-resistant, can be removed without residue	
Enclosure material (front)	Scratch resistance 2H (acc. to JIS K 5600), adhesive force 0.011 N/25 mm (acc. to JIS Z 0237)	
Plastic	Yes; Haze 11.9% acc. to JIS K 7136 and transmission 90.5% acc. to JIS K 7361-1	
• PET	Yes; Basic foil, storage life > 1 year	
Dimensions		
Width	206 mm	
Height	150 mm	
Thickness	0.225 mm; Corners radius 3.1 mm	
Weights		
Weight (without packaging)	8 g; Per unit	
Weight (with packaging)	140 g; Complete set	
Scope of supply		

Delivery quantity in pieces	5; Units per set
Components included	5x removers, 5x cleaning cloths, 1x spatula for applying
Other	
printable with laser printer	No
Merchandise	Yes; URM55 reflection shield, matte
Manufacturer name	Bedifol GmbH
Manufacturer's address	Byk-Gulden-Straße 2 // F22, 78467 Constance, Germany
contacting the manufacturer	phone: +49 (7531) 12738-60, email: shop@schutzfolien24.de
Target devices	Panels and IPC with start of delivery from 2020 (WFP2.3)
Note:	Surface-adhesive film, can be trimmed, printable, observe target device manual before attaching, limited suitability for resistive touch systems
Usable in the following products	
Product 1	6AV2128-3GB06-0AX0
Product 2	6AV2128-3GB36-0AX0

8/24/2021

last modified: