




VMTSC125-75-M16-55-Z

Ruland VMTSC125-75-M16-55-Z, Vibration Isolation Mount, 125mm OD, M16 Threaded Stud, M16 Tapped Hole, 41mm Stud Length, 16mm Tapped Hole Depth, 75mm Height, 55 Shore A Natural Rubber Jacket, Steel



Description

Ruland VMTSC125-75-M16-55-Z is a vibration isolation mount with one tapped hole and one threaded stud. It has a 125mm outside diameter, M16 threaded stud, M16 tapped hole, 41mm stud length, 16mm tapped hole depth, and 75mm height. This vibration isolation mount is used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. It is often referred to as a sandwich mount or rubber buffer because it functions as shock or vibration isolator sandwiched between two machine components or surfaces. The threaded stud side of VMTSC125-75-M16-55-Z can be mounted to the system by passing it through an unthreaded hole and securing with a nut or threading it directly into tapped hole on the component it will be mounted to. The tapped hole can be mounted to the system by threading it onto an existing stud on the component. VMTSC125-75-M16-55-Z has a rubber jacket that is made from natural rubber which has good elasticity and is well suited for most industrial equipment. It has 55 Shore A hardness for a balance of rigidity and shock absorption. The zinc plated steel body allows for high strength and is suitable for most industrial applications. VMTSC125-75-M16-55-Z is manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Outer Diameter (OD)	4.92 in (125 mm)	Height (H1)	2.95 in (75 mm)
Thread (TH)	M16 x 2.0	Plate Thickness (PT)	0.12 in (3 mm)
Stud Length (LS)	1.61 in (41 mm)	Tapped Hole Depth (LT)	0.63 in (16.1 mm)
Spring Rate	5910.01 lb/in (1035 N/mm)	Shore Hardness	55A (+/- 5)
Max Deflection	0.74 in (18.8 mm)	Max Axial Load	4370.29 lb (19440 N)
Geometry	Cylindrical	Rubber Material	Natural Rubber
Metal Material	Zinc Plated Steel	Metallic Body Finish	Zinc-Plated
Country of Origin	Hungary	Weight (lbs)	3.476700
UPC	634529354421	Tariff Code	4016.99.6000
UNSPC	31162804		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		