



Cross-connection rail, No. of poles: 3, Mounting type: Can be screwed on, Width: 32 mm, Colour: natural

### Business data

Article number	2367.0
Article name	QS 3
GTIN (EAN)	4044211051556
Packaging unit	50
Quantity unit	PC
Weight per piece (not including packaging)	2.4 g
Weight per piece (including packaging)	2.41 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	Cross-connection rail
Colour	Natural

---

### Technical data

---

#### Dimensions

Length	6 mm
Width	32 mm
Height	2 mm
Hole diameter	3.4 mm
Hole spacing (mid-point to mid-point)	11.9 mm
Pitch size	12 mm

#### Connection data

No. of poles	3
--------------	---

#### Materials

Material	Brass
Surface	Nickel

#### Further technical data

Mounting type	Screwable
Number of bridged terminals	3

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes

---

**Media**

---

### Accessories

#### ##INVERSE##CONTA-CONNECT




Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1004.4</u>	SK 1/35 24V AC LED(RD) PA-G BK	4044211129989	20 ST



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1119.4</u>	SK 1/35 48V AC LED(RD) PA-G BK	4044211130008	20 ST



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1380.4</u>	SK 1/35 24V DC LED(RD) PA-G BK	4044211129972	20 ST



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1067.4</u>	SK 1/35 48V DC LED(RD) PA-G BK	4044211129996	20 ST



Fused terminal with screw cap for indicator fuses 5x25 mm, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1368.4</u>	SK 1/35 m.K. PA-G BK	4044211129811	20 ST



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1067.4</u>	SK 1/35 48V DC LED(RD) PA-G BK	4044211129996	20 ST

### ##INVERSE##CONTA-CONNECT



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1376.4</u>	SK 1/35 115V AC G PA-G BK	4044211129958	20 ST



Fused terminal, Screw connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 10 mm<sup>2</sup>, Width: 12.2 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>1376.4</u>	SK 1/35 115V AC G PA-G BK	4044211129958	20 ST