



Multi-function timing relay, Interface-Relay-Compact (IRC) socket base MFR-IRCP with screw connection, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 12 to 24VAC/DC

Business data

<u>16207.2</u>
MFR IRCP 12-24V AC/DC
4044211187446
10
PC
38 g
38.2 g
G
85369010
IT
Relay socket base with screw connection



16207.2 MFR IRCP 12-24V AC/DC

Technical data	
Dimensions	
Length	94.3 mm
Width	6.2 mm
Height TS 35 / 7.5 with BA	95.4 mm
Ratings	
Overvoltage category	III
Contamination degree	3
Connection data	
Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm²
Wire cross-section single-core (rigid), max.	2.5 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Stripping length	10 mm
orque	0.5 Nm
nput data	
Power supply AC/DC	12 - 24 V
Control pulse length, min.	50 ms
Output data	
Relay contact	1 CO contact
ime functions	
Fime range	0,1 s - 6 h
Setting ranges	4
Accuracy	
Setting tolerance	± 5%
Repeat accuracy	± 1%
Control contact	
nput	Voltage applied, terminals A1-B1
Response threshold	Automatically adjusted to supply voltage
Materials	
Working temperature, min.	-40 °C
Working temperature, max.	50 °C



16207.2 MFR IRCP 12-24V AC/DC

Technical data		
Further technical data		
Status display	✓	
Storage temperature, min.	-25 °C	
Storage temperature, max.	70 °C	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-01-17	
REACH Candidate Substance Note	No	
RoHS Conform	yes	




16207.2 MFR IRCP 12-24V AC/DC

Approvals	
Standards and regulations	
CE compliant	yes



16207.2 MFR IRCP 12-24V AC/DC

Media







Accessories

Relays



Plug-in miniature power relay, With multi-layer gold contact, 1 CO contact, Input voltage: 12 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
15558.2	PRC 1/12V DC Au	4044211118389	10 ST



Plug-in miniature power relay, With multi-layer gold contact, 1 CO contact, Input voltage: 24 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
15559.2	PRC 1/24V DC Au	4044211118396	10 ST



Plug-in miniature power relay, With power contact, 1 CO contact, Input voltage: 12 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
15501.2	PRC 1/12V DC	4044211118136	10 ST



Plug-in miniature power relay, With power contact, 1 CO contact, Input voltage: 24 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
15502.2	PRC 1/24V DC	4044211118143	10 ST

Adapter



Plug adapter for Interface-Relay-Compact (IRC), ribbon plug-in connector, 14-poles, according to IEC 60603-13, for 8 relay channels, Positive switching, Rated voltage: 24 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
16229.2	FCA/IRC	4044211187682	10 ST

Fuse modules







Interface-Relay-Compact (IRC) fuse module to combine with IRCP, FIRCP, MFR-IRCP and MFR-FIRCP relays and socket bases, for holding 5x20 fuse, Voltage: 250 V, Current: 6 A

Article number	Article name	GTIN (EAN)	Packaging unit
16208.2	SM-IRC	4044211187637	10 ST

Cross-connector





Article number	Article name	GTIN (EAN)	Packaging unit
16209.4	AQI/IRC/16 BK	4044211187651	10

Partition plate



Partition plate for Interface-Relay-Compact (IRC) for separating relay blocks, variable width: 1.5 or 6.2 mm

Article number	Article name	GTIN (EAN)	Packaging unit
16228.2	TW/IRC	4044211187675	10 ST

Quick marking



Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White

Article number	Article name	GTIN (EAN)	Packaging unit
3884.7	MC GS 6x12 R WH	4044211154547	600 ST



Device and installation markers / Maxicard, Length: 6 mm, Width: 12 mm, Colour: White

Article number	Article name	GTIN (EAN)	Packaging unit
3885.7	MC GS 6x12 R So WH	4044211154554	600 ST

Screwdriver

Data sheet 16207.2 MFR IRCP 12-24V AC/DC



Screwdriver with bare blade, Colour: Black-grey



Article number	Article name	GTIN (EAN)	Packaging unit
<u>1086.0</u>	SDB 0,6x3,5	4044211014797	1 ST