

VIEW ON MATING SIDE

∩	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
∩																	
∩	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

A = 16 CONTACTS L=2,8
 C = 16 CONTACTS L=2,8

S = 32 TOTAL NUMBER OF CONTACTS

Marking	Standard
Performance level	G2/0 = Contact area level2 / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	SDA-85052-0001 sht.1
Technical Data	PS-85052-0001

C	G2/0
A	G2/0
Contact symbol	Perform. level
Contact position number	

first release see ECN No. 2249	REVISIONS	FOR PREVIOUS REVISIONS SEE MRI LIST
▷	LTR	

UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ±2°	DRWG BY	SIGN
INCH	KN	
METRIC	CHK'D BY	SIGN
3 PLACE ± .	TB	
2 PLACE ± .	APP'D BY	SIGN
1 PLACE ± .		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SCALE	
DESIGN DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN.		
EQUIVALENT DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN.		
IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY		

REVISE ONLY ON CAD SYSTEM	SH. REV.
CAD/CAM PROJECT NAME S8505202 SO1	THIS DRAWING CONTAINS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
TITLE 96 pos. female connector acc. DIN 41612 style R contacts arrangement	
MOLEX® MOLEX EUROPE	SHEET NO. DATE 1 OF 1 96/09/17
85052-0206	DWG NO. SDA-85052-0206
PART NO.	SIZE A