ATGBICS EX-QSFP-40GE-DAC-1M Juniper Compatible Direct Attach Copper Twinax Cable 40G QSFP+ (1m, Passive)

Brand : ATGBICS Product code: EX-QSFP-40GE-DAC-1M-C

Product name: EX-QSFP-40GE-DAC-1M Juniper Compatible Direct Attach Copper Twinax Cable 40G QSFP+ (1m, Passive)

EX-QSFP-40GE-DAC-1M Juniper Compatible Direct Attach Copper Twinax Cable 40G QSFP+ (1m, Passive)

ATGBICS EX-QSFP-40GE-DAC-1M Juniper Compatible Direct Attach Copper Twinax Cable 40G QSFP+ (1m, Passive):

ATGBICS EX-QSFP-40GE-DAC-1M compatible 40GBase-CU QSFP+ to QSFP+ direct attach cable operates over passive copper with a cable length of 1M. It is suitable for short reach connection between two QSFP+ ports in 40G interconnecting networking applications. Our product meets the specification of Juniper EX-QSFP-40GE-DAC-1M= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; 40G InfiniBand 8x DDR, 4x QDR, IEEE 802.3ba 40Gigabit Ethernet, Fibre Channel, MSA QSFP+ SFF-8436 compliant.

ATGBICS EX-QSFP-40GE-DAC-1M Juniper Compatible Direct Attach Copper Twinax Cable 40G QSFP+ (1m, Passive). Cable length: 1 m, Connector 1: QSFP+, Connector 2: QSFP+, Data transfer rate: 40000 Mbit/s







| Features | | Features | |
|---|--|---|--|
| Product colour * | Black | Country of origin | United Kingdom |
| Cable length * Connector 1 * | tor 1 * QSFP+ tor 2 * QSFP+ tor 1 gender * Male tor 2 gender * Male naterial Polyvinyl chloride (PVC) tor material Copper ti interface type 40 Gigabit Ethernet king standards IEEE 802.3ba re size 30 ansfer rate 40000 Mbit/s d Play | Operational conditions | |
| Connector 2 * Connector 1 gender * Connector 2 gender * lacket material | | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) | 0 - 70 °C -40 - 80 °C 10 - 90% 10 - 85% |
| Conductor material | | Packaging data | |
| Ethernet interface type | | Quantity per pack | 1 pc(s) |
| Networking standards | | Technical details | |
| AWG wire size Data transfer rate Plug and Play Certification | | Sustainability compliance Sustainability certificates Doesn't contain | √ RoHS Lead |



5056468749161

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.