Data sheet 3722.5 ZQI 4/4 BU





Insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 22.3 mm, Rated cross-section: 4 mm², Colour: Blue

RAL: Ähnlich 5005

Business data

| Article number | <u>3722.5</u> |
|--|---------------------------|
| Article name | ZQI 4/4 BU |
| GTIN (EAN) | 4044211111472 |
| Packaging unit | 20 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 2.79 g |
| Weight per piece (including packaging) | 2.85 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | CZ |
| Prio-Article | 3722.8 |
| Product description | Insulated cross-connector |
| | |

Data sheet





| Technical data | |
|----------------------------------|---------------|
| <u>Dimensions</u> Length | 4.5 mm |
| Width | 22.3 mm |
| Pitch size | 6 mm |
| | O IIIIII |
| Ratings | 000 1/ |
| Voltage with partition, max. | 800 V |
| Voltage without partition, max. | 800 V |
| Rated current | 32 A |
| Rated cross-section | 4 mm² |
| Contamination degree | 3 |
| Connection data | |
| No. of poles | 4 |
| Materials | |
| Material | Copper alloy |
| Surface | Tin-plated |
| Insulation housing | Polyamide 6.6 |
| Flammability class UL 94 | V-2 |
| Working temperature, min. | -40 °C |
| Working temperature, max. | 105 °C |
| Further technical data | |
| Mounting type | Plug in |
| Insulation available | ✓ |
| Touch protection is available | ✓ |
| Number of bridged terminals | 4 |
| Environmental Product Compliance | |
| REACH Conform | yes |
| REACH Reference date | 2022-06-10 |
| REACH Candidate Substance Note | No |
| RoHS Conform | yes |

Data sheet 3722.5 ZQI 4/4 BU



Media

Data sheet

3722.5 ZQI 4/4 BU



Accessories

##INVERSE##CONTA-CONNECT



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| 3515.2 | ZRK 4/2A BG | 4044211151751 | 100 |



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|-------------------|
| 1716.2 | ZRK 4/2A Ex BG | 4044211058579 | 100 |



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|-------------------|
| <u>1717.2</u> | ZRK 4/3A Ex BG | 4044211058609 | 100 |



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>3516.2</u> | ZRK 4/3A BG | 4044211151775 | 100 |



Ex feed-through terminal ATEX-certified, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|-------------------|
| <u>1718.2</u> | ZRK 4/4A Ex BG | 4044211058630 | 100 |



Feed-through terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 4 mm², Width: 6.1 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|-------------------|
| <u>3517.2</u> | ZRK 4/4A BG | 4044211151782 | 100 |