

Han-Eco 16B-Cover-for DL-w. cord-HBM-HSM



Part number	19 43 016 5425
Specification	Han-Eco 16B-Cover-for DL-w. cord- HBM-HSM
HARTING eCatalogue	https://b2b.harting.com/19430165425

Image is for illustration purposes only. Please refer to product description.

Identification

REACH Annex XVII substances

Category	Accessories
Series of hoods/housings	Han-Eco [®] B
Type of hood/housing	Protection cover
Description of hood/housing	for bulkhead mounted housings for surface mounted housings
Version	
Size	16 B
Locking type	Double locking lever
Technical characteristics	
Limiting temperature	-40 +125 °C
Number of relockings	≥500
Degree of protection acc. to IEC 60529	IP66
Material properties	
Material (hood/housing)	Polyamide (PA) Fibre-glass reinforced
Colour (hood/housing)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e

Page 1 / 2 | Creation date 2023-02-07 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany

Not contained



Material properties

REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

Specifications and approvals

Specifications	IEC 61984
	EN 45545-2 Fire protection on railway vehicles

Commercial data

Packaging size	1
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140192225
eCl@ss	27440208 Cap for industrial connectors