


Specification Sheet

Part Number: MB50C2



Compact size fits most mounting applications.

Simple to install with a screw or rivet.

Single hole attachment with two-way entry for cable tie.

Screw Mount Cable Tie Base, 1.49" x 1.49", 0.35" Max Tie Width, 0.19" Hole Dia, PA66, Black, 100/pkg

Article Number 151-28500

Type MB5

Color Black (BK)

Quantity Per bag

Product Description These cable tie mounts are compact in size. They are designed for simple yet robust installation. They pair with a cable tie for mounting applications including telecom equipment, switchgear and control cabinets.

Short Description Screw Mount Cable Tie Base, 1.49" x 1.49", 0.35" Max Tie Width, 0.19" Hole Dia, PA66, Black, 100/pkg

Global Part Name MB5-PA66-BK

| | |
|---------------------------------------|--------------------------|
| Length L (Imperial) | 1.49 |
| Length L (Metric) | 37.7 |
| Fixation Method | Screw Mounting and Rivet |
| Width W (Imperial) | 1.49 |
| Width W (Metric) | 37.7 |
| Cable Ties | T18 - T150 |
| Height H (Imperial) | .25 |
| Height H (Metric) | 6.20 |
| Cable Tie Width Max (Imperial) | 0.35 |
| Cable Tie Width Max (Metric) | 8.9 |
| Mounting Hole Diameter D (Imperial) | 0.19 |
| Mounting Hole Diameter D (Metric) | 4.8 mm |
| Mounting Hole Diameter D Max (Metric) | 4.8 |
| Mounting Hole Centers (Imperial) | 1.0 |

| | |
|-------------------------------|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V-2 |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| Certification/Specification | UL |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |