

Ph: (262)883-9060 sales@reedswitchdevelopments.com


SPECIFICATION SHEET

2020-4100-000

Alternate Part Number: **AM2020-4100-00-01**

Active / Equivalent Part Numbers: 2020-4100-000 - Magnetic Actuator Only AM2020-4100-00-01 - Magnetic Actuator Only

2020 Series Magnetic Reed Switch Actuator



All measurements are in inches [millimeters]

Specifications	Description	UM
Shape	Rectangular w/ Mounting Holes	
Length	2.625"/66.68mm	in/mm
Width	0.340"/8.64mm	in/mm
Height	0.340"/8.64mm	in/mm
Housing Material	Celanex 3316	
Magnetic Orientation	Through Length	
Max Operating Temperature	975/525	°F/°C
Max Operating Temperature Curie Temperature BR max	1580/860	°F/°C
BR max	12.8	kGauss
BH max	5.5	MGOe
Coercive Force Hc	640	kOe
Intrinsic Coercive Force Hci	640	kOe

Assembly Certifications

RoHS / REACH Compliant	Υ
Conflict Free Material	Υ

REV DATE: 10/06/2021

DISCLAIMER NOTICE: INFORMATION FURNISHED IS PROPRIETARY, AND IS BELIEVED TO BE ACCURATE AND RELIABLE, AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IT SHALL BE THE RESPONSIBILITY OF THE BUYER TO ENSURE THAT THE GOODS ARE SUFFICIENT AND SUITABLE FOR THE PURPOSE OR PURPOSES INTENDED (WHETHER BY THE BUYER OR BY ANY THIRD PARTY) AND THAT THEIR CAPACITY AND PERFORMANCE IS NOT ADVERSELY AFFECTED BY ANY ITEMS USED IN THEIR INSTALLATION (WHERE RELEVANT) AND/OR IN CONNECTION WITH THEM.