



All dimensions are in mm; tolerances acc. to ISO 2768 m-H

**Interface**

According to

Rosenberger EBC™

**Documents**

Application note

EBC

**Material and plating**

**Connector parts**

- Center contact
- Outer contact
- Dielectric

**Material**

- Cu
- Brass
- PTFE

**Plating**

- Silver ≥ 1,5 µm
- Flash white bronze over silver(e.g. Optargen®)

**Electrical data**

Impedance	50 Ω
Frequency	DC to 8 GHz
Return loss	≥ 26 dB @ DC to 6 GHz <sup>1)</sup>
Insertion loss	≤ 0.05 x √f [GHz] dB
Insulation resistance	≥ 5 GΩ
Center contact resistance	≤ 10 mΩ
Outer contact resistance	≤ 5 mΩ
Test voltage (at sea level)	500 V rms
Working voltage (at sea level)	335 V rms
Power handling (sea level, VSWR 1.0)	100 W @ 3.5 GHz @ 105°C <sup>2)</sup>
Contact Current	≤ 2A DC
Screening attenuation - Interface	≥ 50 dB up to 4 GHz
Intermodulation (3 <sup>rd</sup> order)	≥ 160 dBc (2 x 43 dBm)

1) Dependent on axial misalignment

2) Power value is dominated by the application

**Mechanical data**

Mating cycles	≥ 50
Center contact captivation	≥ 5 N
Engagement force	
-Limited detent	≤ 35N (typ.30N)
-smooth bore	≤ 12N
Disengagement force	
-Limited detent	≤ 12N
-smooth bore	≤ 5N
Working range	1.6 mm (± 0.8 mm)
Radial misalignment	max. 4°
Pitch	≥ 6.9 mm

**Environmental data**

Temperature range	-55 °C to +105 °C
Thermal shock	MIL-STD-202, Method 107, Condition B
Climatic category	IEC 61169-1, Sub-clause 9.4.5
Moisture resistance	MIL-STD-202, Method 106
Vibration	MIL-STD-202, Method 204, Condition B
Shock	MIL-STD-202, Method 213, Condition A
RoHS	compliant

**Weight**

Weight	0.55 g/pc
--------	-----------

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
M. Schmid	09.01.19	B_Aicher	01.09.20	d00	20-1267	T_Stadler	01.09.20
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>						Tel. : +49 8684 18-0 Email : <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>	
						Page 2 / 2	