

**product type designation**

product description

**PROFIBUS Plastic Fiber Optic standard cable**

Fiber-optic cable with polyoptical fiber, 100m ring, unassembled

PROFIBUS Plastic Fiber Optic (980/1000), standard cable, 100 m ring.



suitability for use

Cable for indoor applications

version of the assembled FO cable

For assembly with four Simplex connectors

cable designation

I-V4Y(ZN)Y 2P 980/1000

wire length

100 m

**optical data**

attenuation factor per length

- at 650 nm / maximum
- at 660 nm / maximum

160 dB/km  
230 dB/km

bandwidth length product

- at 650 nm

1 GHz·m

**mechanical data**

number of fibers / per FOC core

1

number of FO cores / per FOC cable

2

version of the FO conductor fiber

Step index fiber 980/1000 μm

outer diameter

- of the optical fibers
- of the optical fiber sheath
- of the FOC core sheath

980 μm  
1000 μm  
2.2 mm

symmetrical deviation / of the outer diameter of the FOC core sheath

0.1 mm

outer diameter / of the cable

7.8 mm

symmetrical deviation / of the outer diameter of the line

0.3 mm

material

- of the fiber-optic cable core
- of the optical fiber sheath
- of the FOC core sheath
- of the fiber-optic cable sheath
- of the strain relief

Polymethylmethacrylate (PMMA)  
Fluoridated special polymer  
PA  
PVC  
Kevlar fibers

color

- of the FOC core sheath
- of cable sheath

orange/black  
Violet

bending radius

- with single bend / minimum permissible
- with multiple bends / minimum permissible

100 mm  
150 mm

tensile load

- during installation / short-term
- during operation / maximum

100 N  
100 N

short-term shear force per length	100 N/cm
weight per length	65 kg/km
<b>ambient conditions</b>	
ambient temperature	
• during operation	-30 ... +70 °C
• during storage	-30 ... +70 °C
• during transport	-30 ... +70 °C
• during installation	50 °C
fire behavior	flame-resistant acc. to IEC 60332-1-2
class of burning behaviour / according to EN 13501-6	Eca
chemical resistance	
• to mineral oil	conditional resistance
• to grease	conditional resistance
radiological resistance / to UV radiation	not resistant
<b>product features, product functions, product components / general</b>	
product feature	
• halogen-free	No
• silicon-free	Yes
product component / rodent protection	No
wire length	
• for POF FOC / with PROFIBUS / maximum	80 m
<b>standards, specifications, approvals</b>	
certificate of suitability	
• UL approval	Yes
• RoHS conformity	Yes
reference code	
• according to IEC 81346-2	WH
• according to IEC 81346-2:2019	WHA
<b>further information / internet-Links</b>	
Internet-Link	
• to web page: selection aid TIA Selection Tool	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>
• to website: Industrial communication	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
• to website: Industry Mall	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Selection guide for cables and connectors	<a href="https://sie.ag/2QdLxcP">https://sie.ag/2QdLxcP</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>last modified:</b>	5/10/2022 