



Limit switch, 9007, 240 VAC 10amp ms +options

9007MS05S0500

Main

Range of product	9007
Series name	Miniature potted
Product or component type	Limit switch
Device short name	9007MS/ML
Sensor design	Miniature
Body type	Fixed
Head type	Multi-directional head
Material	Metal
Body material	Cast zinc
Number of poles	1

Complementary

Fixing mode	By the body
Movement of operating head	Multi-directional
Type of operator	Spring return wire whisker steel -
Type of approach	Multi-directional approach
Switch actuation	By any moving part
Contacts type and composition	NC-NO
Switch function	SPDT
Contact form	Form C
Contacts material	Silver contacts
Contact operation	Snap action
Positive opening	Without
Electrical connection	Pre-wired cable bottom
Type of cable	SJTO cable (AWG 18), 5.49 m, yellow
Terminals description ISO n°1	(black)com (white)NO (green-yellow)gnd (red)NC
Wire insulation material	PVC
Maximum force for tripping	15 ozf

6 A at 120 V AC, A300 conforming to NEMA rating designation 3 A at 240 V AC, A300 conforming to NEMA rating designation 5 A at 28 V DC	
10 A	
300 V (pollution degree 3) conforming to UL 508 300 V (pollution degree 3) conforming to CSA C22.2 No 14	
100000 cycles	
10000000 cycles	
UL CE CSA	
1	
44.45 mm	
39.62 mm	
15.75 mm	
0.54 kg	
35 gn for 9 ms conforming to IEC 60068-2-27	
10 gn (f= 751200 Hz) conforming to IEC 60068-2-6	
NEMA 1 conforming to Nema type 250 NEMA 12 conforming to Nema type 250 NEMA 13 conforming to Nema type 250	
IP54 conforming to IEC 60529	
-40104 °C	
-40104 °C	
Epoxy powder coat	
CE UL CSA	
LR 25490 Class 32 11 03 E78403	
PCE	
1	
77.419 cm	
30.48 cm	
196.645 cm	
544.311 g	
Green Premium product	
REACh Declaration	
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Yes	
Yes	
	3 A at 240 V AC, A500 conforming to NEMA rating designation 5 A at 28 V DC 10 A 300 V (pollution degree 3) conforming to UL 508 300 V (pollution degree 3) conforming to CSA C22.2 No 14 1000000 cycles 10000000 cycles UL CE SSA 1 44.45 mm 39.62 mm 15.75 mm 0.54 kg 35 gn for 9 ms conforming to IEC 60068-2-27 10 gn (f= 751200 Hz) conforming to IEC 60068-2-6 NEMA 12 conforming to Nema type 250 NEMA 13 conforming to Nema type 250 NEMA 13 conforming to IEC 60529 -40104 °C -40104 °C Epoxy powder coat CE UL CSA PCE 1 77.419 cm 30.48 cm 196.645 cm 544.311 g Green Premium product REACh Declaration Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration Yes

Environmental Disclosure	Product Environmental Profile
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Contractual warranty	
Warranty	18 months

Recommended replacement(s)