



CORE DIMENSIONS		35T0135-60P			
UNCOATED CORE					
		MM	INCHES	MM	INCHES
OD	3.43	(.135)	±	.13	(.005)
ID	1.78	(.070)	±	.13	(.005)
TH	1.52	(.060)	±	.13	(.005)
SINGLE PARYLENE COATING		35T0135-60P			
OD	3.45	(.136)	±	.13	(.005)
ID	1.75	(.069)	±	.13	(.005)
TH	1.55	(.061)	±	.13	(.005)

WEIGHT / K 0.11 LBS  
 INITIAL PERMEABILITY 5000

ELECTRICAL SPECIFICATION								
	MIN ( $\mu$ H)	MIN TOL. (-20%)	NOM ( $\mu$ H)	MAX ( $\mu$ H)	MAX TOL. (+20%)	FREQ. (kHz)	VOLT. (V)	URNS
L	.801	(-20%)	1.001	1.201	(+20%)	100	≤ .00027	1
Q	10	-	-	-	-	100	≤ .00027	1

COATING SPECIFICATIONS			
TYPE	Max. Coating (mils.)	Min. DLB VAC	TEST FORCE (LB)
PARYLENE	0.5	1000	.10

NOTES:

- Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
A	Original Draft	1997/5/18	BAC
B	TRANSFER TO LOTUS NOTES	1997/11/17	IS
C	REMOVE Q COATING SPECS CHANGE P/N	2005/10/13	JRK
D	Revised Template	2006/6/1	WMM
E	Revised Template	2019/3/10	Jcai

Date: 2019/3/10	DWG # 35T0135-60P-E	Rev:
Drawn By: Jcai	Title # 35T0135-60P	E

Laird This document contains information which is proprietary to laird. No production or publication of this document in whole or in part shall be made without written authorization from Laird.