

## Han Ex 3A-QL Kit HSM angled-M20/HTE-M20



Image is for illustration purposes only. Please refer to product description.

Part number	10 36 003 0008
Specification	Han Ex 3A-QL Kit HSM angled-M20/ HTE-M20
HARTING eCatalogue	<a href="https://b2b.harting.com/10360030008">https://b2b.harting.com/10360030008</a>

### Identification

Category	Connector sets
Series	Han A <sup>®</sup>
Series of hoods/housings	Han <sup>®</sup> Ex
Element	Complete set

### Version

Termination method	Han-Quick Lock <sup>®</sup> termination
Size	3 A
Number of contacts	3
PE contact	Yes
Version	Top/side entry
Cable entry	1x M20 1x M20
Locking type	Single locking lever
Field of application	Connectors for explosion hazardous environments

### Technical characteristics

Rated current	10 A
Rated voltage	90 V
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-20 ... +40 °C
Mating cycles	≥500



Pushing Performance  
Since 1945

## Technical characteristics

Degree of protection acc. to IEC 60529 IP67 with seal screw 09 20 000 9918

## Material properties

Material (insert)	Polycarbonate (PC)
Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 5015 (sky blue)
Material (seal)	NBR
Material (locking)	Stainless steel
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead
California Proposition 65 substances	Nickel
California Proposition 65 substances	Naphthalene

## Specifications and approvals

Specifications	IEC 60664-1
Specifications	IEC 61984
Specifications	IEC 60079-0
Specifications	EN 60079-11

## Commercial data

Packaging size	1
Net weight	227 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140189645
eCl@ss	27440113 Rectangular connectors (set)