TRIPP-LITE

IEC C14 to IEC C7 Power Cord Adapter - 7A, 125V, Black

MODEL NUMBER: P016-000



C14 to C7 adapter connects your notebook or laptop with a 2-slot C8 power connector to a C13 outlet on a surge protector or UPS.

Features

IEC C14 to IEC C7 Adapter Connects Notebook Computers to an AC OutletThis UL-listed C14 to C7 power cord adapter converts a C8 plug into a C14 connector and is ideal for a device's built-in power cord that doesn't match an available outlet. You can use this adapter to connect a notebook computer, laptop or other device with a two-slot C8 power cord to a surge protector or UPS system with a C13 outlet.

Specifications

| OVERVIEW | | |
|------------------------------------|----------------------------|--|
| UPC Code | 037332217981 | |
| Device Compatibility | Laptop; Computer; UPS; PDU | |
| Country/Region | North America | |
| INPUT | | |
| Maximum Input Amps | 7 | |
| Voltage Compatibility (VAC) | 125 | |
| PHYSICAL | | |
| Plug Color | Black | |
| Wire Gauge (OD - mm ²) | N/A | |
| Cable Length (ft.) | 0 | |
| Cable Length (m) | 0.00 | |

Highlights

- Recommended for powering notebook computers and laptops with C8 inlets
- Converts a C8 connector into a C14 connector to match an available outlet

Applications

- Connect a laptop or notebook computer to a C13 outlet near your workstation
- Connect a laptop or notebook to a surge protector at a trade show or lecture hall

Package Includes

 P016-000 IEC C14 to IEC C7 Power Cord Adapter, Black

TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

| ſ | |
|---------------------------------|-------------------------------------|
| Shipping Dimensions (hwd / in.) | 5.00 x 3.98 x 0.50 |
| Shipping Dimensions (hwd / cm) | 12.70 x 10.11 x 1.27 |
| Shipping Weight (lbs.) | 0.07 |
| Shipping Weight (kg) | 0.03 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 14° to 140°F (-10° to 60°C) |
| Storage Temperature Range | 14° to 140°F (-10° to 60°C) |
| Operating Humidity Range | 30% to 80% RH |
| Storage Humidity Range | 30% to 80% RH |
| CONNECTIONS | |
| Side A - Connector 1 | IEC-320-C14 |
| Side B - Connector 1 | IEC-320-C7 (NON-POLARIZED) |
| FEATURES & SPECIFICATIONS | |
| Antibacterial | No |
| Angled Plug | No |
| High Voltage | No |
| Locking Plug | No |
| Coiled Power Cord | No |
| STANDARDS & COMPLIANCE | |
| Product Certifications | CSA (Canada); cUL Listed; UL Listed |
| Product Compliance | RoHS; REACH |
| WARRANTY & SUPPORT | |
| | |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.