

Extension Cord Y Splitter, NEMA 5-15P to 2x NEMA 5-15R - 10A, 120V, 18 AWG, 1 ft. (0.31 m), Black

MODEL NUMBER: P022-001-2









Extension cord splitter allows two devices with NEMA 5-15P plugs to share one AC power input cord and one NEMA 5-15R outlet.

Features

Y-Style Power Cord Splitter Connects 2 Devices with 5-15P Plugs to One AC Outlet This extension cable splitter allows two devices with NEMA 5-15P plugs to share one AC input cord and one NEMA 5-15R outlet. The AC power splitter features a 5-15P plug for connecting to an AC power source and two 5-15R ends for connecting to devices' power cords. By connecting two devices to one outlet, the 1-ft. (0.31 m) splitter frees up space in a PDU or surge protector and allows welcome flexibility in placing equipment with respect to the power outlet.

Dual Cable Powers a Wide Variety of Essential ElectronicsWith this extension cord splitter, a single NEMA 5-15R outlet can power two devices, such as computers, monitors, printers, instrument amplifiers and other equipment compatible with a NEMA 5-15P plug. Ideal for areas where AC outlets are limited, such as rack cabinets, this extension cord Y splitter is compatible with Tripp Lite power and extension cords.

Highlights

- Connects 2 devices to one AC outlet to save space and reduce cable clutter
- Recommended for powering dual computers, monitors or other compatible peripherals
- Adds 1-ft. (0.31 m) to your existing power connection to provide flexibility in placing devices
- Ideal replacement for a worn-out or missing extension cord Y splitter
- NEMA 5-15P plug connects to AC power; 5-15R ends connect to devices' cords

Applications

- Connect 2 devices like computers, monitors, scanners and printers to one power outlet up to 1-ft. (0.31 m) away in your home office, work space or dorm room
- Cut cable clutter by powering both monitors in a dual-monitor display mount with a single cord
- Save space in a 0U vertical rack-mount PDU by plugging two rack devices into one outlet

Package Includes

 P022-001-2 Extension Cord Y Splitter, 1-ft. (0.31 m), Black

Specifications

OVERVIEW		
UPC Code	037332138101	
Device Compatibility	Computer; Monitor/HDTV; Printer; Server; UPS; PDU	
Country/Region	North America	
INPUT		
Maximum Input Amps	10	
Voltage Compatibility (VAC)	125	



Plug Color Black Cable Jacket Color Black Cable Jacket Atterial PVC Cable Jacket Rating VW-1 Pvower Cord Jacket Type SJT Cable Jacket Rating VW-1 Pvower Cord Jacket Type SJT Cable Jacket Rating VW-1 Pvower Cord Jacket Type SJT Cable Outer Diameter (DD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (AWG) 18 Wire Gauge (AWG) 18 Vire Gauge (OD - mm²) 0.82 Cable Length (ft.) 1 Cable Length (fm.) 0.30 Shipping Dimensions (fwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (fwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (fwd / in.) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (lbs.) 0.18 ENVIRONMENTAL Operating Temperature Range -4" to 140"F (-20" to 60"C) Coreating Humidity Range 10% to 65% RH Connector 1 10% to 65% RH 10% to 65% RH			
Cable Jacket Color Black Cable Jacket Material PVC Cable Jacket Rating VW-1 Power Carl Jacket Type SJT Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (ft) 1 Cable Length (m) 0.30 Shipping Dimensions (hwd / om) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / om) 25.40 x 17.78 x 1.27 Shipping Weight (bs) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4" to 140°F (-20° to 60°C) Storage Temperature Range -4" to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angied Plug No Locking Plug No	PHYSICAL		
Cable Jacket Naterial PVC Cable Jacket Rating VW-1 Power Cord Jacket Type SJT Cable Outer Diameter (DD) 7,8mm Number of Conductors 3 Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (AWG) 18 Wire Gauge (AWG) 18 Wire Gauge (DO - mm²) 0,82 Cable Length (ft.) 1 Cable Length (m) 0,30 Shipping Dimensions (hwd / in.) 1,000 x 7,00 x 0,50 Shipping Dimensions (hwd / cm) 25,40 x 17,78 x 1,27 Shipping Weight (ba.) 0,40 Shipping Weight (ba.) 0,40 Shipping Weight (ba.) 0,18 ENVIRONMENTAL Operating Temperature Range 4* to 140°F (-20° to 60°C) Storage Temperature Range 10% to 65% RH Storage Hunidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No Locking Plug No Colled Power Cord No	Plug Color	Black	
Cable Jacket Rating VW-1 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (AWG) 18 Wire Gauge (AWG) 19 Cable Length (ft.) 1 Cable Length (ft.) 1 Cable Length (m) 0.30 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Operating Temperature Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Artibacterial No Angled Plug No Locking Plug No Locking Plug No Colled Power Cord No	Cable Jacket Color	Black	
Power Cord Jacket Type SJT Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (AWG) 0.82 Cable Length (h.) 1 Cable Length (h.) 1 Cable Length (m) 0.30 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (bs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Operating Temperature Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Artibacterial No Angled Plug No Locking Plug No Locking Plug No Colled Power Cord No STANDARDS & COMPLIANCE	Cable Jacket Material	PVC	
Cable Outer Diameter (OD) 7.8mm Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (ft.) 1 Cable Length (m) 0.30 Shipping Dimensions (thwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (thwd / in.) 25.40 x 17.78 x 1.27 Shipping Weight (bs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4º to 140°F (-20° to 60°C) Storage Temperature Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Colled Power Cord No STANDARDS & COMPLIANCE	Cable Jacket Rating	VW-1	
Number of Conductors 3 Wire Gauge (AWG) 18 Wire Gauge (OD - mm²) 0.82 Cable Length (ft.) 1 Cable Length (m) 0.30 Shipping Dimensions (twd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (twd / in.) 25.40 x 17.78 x 1.27 Shipping Weight (bs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Colled Power Cord No STANDARDS & COMPLIANCE	Power Cord Jacket Type	SJT	
Wire Gauge (AWG) 18 Wire Gauge (DD - mm²) 0.82 Cable Length (ft.) 1 Cable Length (m) 0.30 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No Locking Plug No Locking Plug No Colled Power Cord No	Cable Outer Diameter (OD)	7.8mm	
Wire Gauge (OD - mm²) 0.82 Cable Length (ft.) 1 Cable Length (m) 0.30 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side B - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Number of Conductors	3	
Cable Length (ft.) 1 Cable Length (m) 0.30 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No Locking Plug No Coiled Power Cord No	Wire Gauge (AWG)	18	
Cable Length (m) 0.30 Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No Locking Plug No Colled Power Cord No STANDARDS & COMPLIANCE	Wire Gauge (OD - mm²)	0.82	
Shipping Dimensions (hwd / in.) 10.00 x 7.00 x 0.50 Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (lbs.) 0.40 Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range 10% to 65% RH Storage Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No Locking Plug No Colied Power Cord No STANDARDS & COMPLIANCE	Cable Length (ft.)	1	
Shipping Dimensions (hwd / cm) 25.40 x 17.78 x 1.27 Shipping Weight (kg) 0.40 Shipping Weight (kg) ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug No Colled Power Cord No	Cable Length (m)	0.30	
Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Colied Power Cord No STANDARDS & COMPLIANCE	Shipping Dimensions (hwd / in.)	10.00 x 7.00 x 0.50	
Shipping Weight (kg) 0.18 ENVIRONMENTAL Operating Temperature Range -4° to 140°F (-20° to 60°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Shipping Dimensions (hwd / cm)	25.40 x 17.78 x 1.27	
ENVIRONMENTAL Operating Temperature Range	Shipping Weight (lbs.)	0.40	
Operating Temperature Range	Shipping Weight (kg)	0.18	
Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug No Coiled Power Cord No	ENVIRONMENTAL		
Operating Humidity Range 10% to 65% RH Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Operating Temperature Range	-4° to 140°F (-20° to 60°C)	
Storage Humidity Range 10% to 65% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug No Coiled Power Cord No	Storage Temperature Range	-4° to 140°F (-20° to 60°C)	
CONNECTIONS Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Operating Humidity Range	10% to 65% RH	
Side A - Connector 1 NEMA 5-15P Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Storage Humidity Range	10% to 65% RH	
Side B - Connector 1 (2) NEMA 5-15R FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug No Coiled Power Cord No	CONNECTIONS		
FEATURES & SPECIFICATIONS Antibacterial No Angled Plug No High Voltage No Locking Plug No Coiled Power Cord No	Side A - Connector 1	NEMA 5-15P	
Antibacterial No Angled Plug No High Voltage No Locking Plug No Coiled Power Cord No	Side B - Connector 1	(2) NEMA 5-15R	
Angled Plug No High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	FEATURES & SPECIFICATIONS		
High Voltage No Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Antibacterial	No	
Locking Plug No Coiled Power Cord No STANDARDS & COMPLIANCE	Angled Plug	No	
Coiled Power Cord No STANDARDS & COMPLIANCE	High Voltage	No	
STANDARDS & COMPLIANCE	Locking Plug	No	
	Coiled Power Cord	No	
	STANDARDS & COMPLIANCE		
Product Certifications cUL Listed; UL Listed	Product Certifications	cUL Listed; UL Listed	



Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.