# **6X4X4 IMPACT® LINE**





Mechanical and Thermal	Test Spec.	Unit	Impact® Line
Instrumented Dart Impact @ 73° F		in/lb.	565
Falling Ball Impact @ 73° F	UL-746	in/lb.	900
Deflection Temperature @ 264 psi	ASTM D648	Deg. F	270
Modulus of Elasticity	ASTM D790	ksi	340
Temperature Range		Deg. F	-40 to 265

## **IMPACT®**

## **Features and Benefits**

- Standard Color light gray with a high gloss finish
- Best material bases, opaque covers and clear covers are all made of high-impact, UV resistant polycarbonate
- Easy ordering One part number equals one completely assembled enclosure
- Super easy use mounting flanges integral, so no extra hardware needed
- Flexible Interior Mounting bosses on rear wall and lid of opaque enclosure provide multiple mounting options for din rail, back panels, or other components
- Advanced face plate mounting system Brand new completely unique and easy
- Secure Choose your level of protection: pad lockable, tamper screw or tamper tag capable
- Frequency Friendly Available with absolutely no metals of any kind on the enclosure which is extremely favorable for sending and receiving wireless signals
- UL-50 / c-UL Listed (file # E207562)

Our Impact® Line enclosures are the most versatile, feature packed, aesthetically pleasing, NEMA UL rated, non-metallic enclosures available. Features like extremely durable, UV resistant, wide temperature range, easy to machine, lighter than other non-metallic or metal materials, the "Made in USA" Impact® Line enclosures provide great value to any application.










Flammable / UV Ratings	Test Spec.	Unit	Impact® Line
Flame Rating - UL	UL 94		5VA
Outdoor UV Exposure	UL	-	f1


6044 P/N	4X IP66	6P IP68	Clear Cover	Opaque Cover	Integrated Mounting Flange	Standard Hinge	Low Profile Hinge	Integrated Locking Latch	Stainless Steel Locking Latch	Non-Metallic Locking Latch	Face Plate Mtg System*
P6044	✓	✓		✓	✓	✓		✓			✓
P6044C	✓	✓	✓		✓	✓		✓			✓
P6044LL	✓			✓	✓	✓			✓		✓
P6044CLL	✓		✓		✓	✓			✓		✓
P6044LP	✓	✓		✓	✓		✓	✓			✓
P6044LPC	✓	✓	✓		✓		✓	✓			✓
P6044LPLL	✓			✓	✓		✓		✓		✓
P6044LPCLL	✓		✓		✓		✓		✓		✓
P6044NL	✓			✓	✓	✓				✓	✓
P6044CNL	✓		✓		✓	✓				✓	✓
P6044LPNL	✓			✓	✓		✓			✓	✓
P6044LPCNL	✓		✓		✓		✓			✓	✓


\* Sold separately



# **6X4X4 IMPACT® LINE**







Register online to download this drawing off the integra website at www.integraenclosures.com | Your company's logo or other information on the lid. Consult factory for details.

# Accessories for 6x4x4 Impact® (For complete accessories, see pages 78-81)



### **Back Panels**

ABP64-IMP - Aluminum panel SBP64-IMP - Steel panel PVCBP64-IMP - PVC panel



## **Aluminum Face Plate System**

AFPK64-IMP - Aluminum face plate and FPSK-55 mounting kit AFP64-IMP - Aluminum face panel only



Face Plate Support Kit CB64-IMP - Support kit contains 4 support panels and 8 screws.



### Air Vents

VENT 3 - Aluminum louvered VENT 2 - Outdoor labyrinth



Steel Face Plate System
SFPK64-IMP - Steel face plate
and FPKR-55 mounting kit SFP64-IMP - Steel face panel only



## Hole Plugs

Liquid tight thru plugs. IP67 and UL rated. See page 72 for more



DIN 6-IMP - 2 rails, 4 screws



## **Pole Mounting Kit**

PMKG-26-IMP - 2" pole PMKG-36-IMP - 3" pole PMKG-46-IMP - 4" pole PMKG-126-IMP - 12" pole



## **Cord Grips**

IP68/NEMA 4X/6P rated See page 72 for more details.