




USSK32-12-8-SS

Ruland USSK32-12-8-SS, 3/4" x 1/2" Single Universal Joint, Friction Bearing, Stainless Steel, Set Screw With Keyway, 1.995" OD, 5.500" Length





Description

Ruland USSK32-12-8-SS is a single cardan friction bearing universal joint with 0.7500" x 0.5000" bores, 3/16" x 1/8" keyways, 1.995" OD, 5.500" length, and 3/8-16 set screws. It is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. USSK32-12-8-SS is made from high grade stainless steel for increased corrosion resistance. It can be combined with boot UBOOT32/51-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

P	roc	luct	Sne	cific	ation	9
	100	ıucı	ONG	CIIIC	auvii	3

0.7500 in	Small Bore (B2)	0.5000 in	
3/16 in	Keyway (K2)	1/8 in	
1.700 in	B2 Max Shaft Penetration	1.700 in	
1.995 in	Bore Tolerance	+0.0010 in / -0.0000 in	
5.500 in	Yoke Length (LY)	2.750 in	
1.700 in	Broached Set Screw	3/8-16	
Bright	Peak Torque	15,600 in-lb	
3,120 in-lb	Max Operating Angle	45°	
Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainless Steel	Manufacturer	Belden Universal	
USA	Recommended Lubricant	LUBRIPLATE No. 1200-2	
UBOOT32/51-NI-KIT	UPC	63452934198	
8483.60.4000	UNSPC	25173810	
Performance ratings are for guidance only. The user must determine suitability for a particular application.			
▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov .			
	3/16 in 1.700 in 1.995 in 5.500 in 1.700 in Bright 3,120 in-lb Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainless Steel USA UBOOT32/51-NI-KIT 8483.60.4000 Performance ratings are for guida WARNING This product can experience of the state of the	3/16 in Keyway (K2) 1.700 in B2 Max Shaft Penetration 1.995 in Bore Tolerance 5.500 in Yoke Length (LY) 1.700 in Broached Set Screw Bright Peak Torque 3,120 in-lb Max Operating Angle Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainless Steel USA Recommended Lubricant UBOOT32/51-NI-KIT UPC 8483.60.4000 UNSPC Performance ratings are for guidance only. The user must determine	