



## Connectors 160/163

### 163 ST/ 3 DS

plug, 3 pole, wire protector (DS): yes, black, voltage rating: 400 V, cross-section rating: 2.5 mm<sup>2</sup>



### Order Info

reference number (ref.no.)	151183
PU	200
EAN	4028012100088

### Type

type	plug
number of poles	3 pole
clamping units per pole	1
colour	black
cross-section rating	2.5 mm <sup>2</sup>
connection type	screw
PE function	yes
protection against incorrect plugging	yes
wire protector (DS)	yes

### Technical Data

voltage rating	400 V
current rating	16 A
impulse voltage rating	4.0 kV
insulating material	PA
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	2.5 mm <sup>2</sup>
flammability rating	V-2
max. ambient temperature operation	70 °C
IP code	IP20
IP code when plugged	IP40
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	6.5-7.0 mm
assembly contact screw	0,6x3,5 / ⚙ 0,5 Nm

## Approvals

<b>acc. to EN 61984</b>	<a href="#">Download PDF</a>
<b>acc. to UL</b>	<a href="#">Download PDF</a>
<b>acc. to CSA</b>	<a href="#">Download PDF</a>

## Accessories

<b>163/ 3 ABK</b>	192303
<b>163/ 3 ZEL</b>	192203