

External insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 50.1 mm, Rated current: 27 A; Colour: Yellow

RAL: 1026

Business data

| | |
|--|------------------------------------|
| Article number | 2029.0 |
| Article name | AQI 10/5/15 YE |
| GTIN (EAN) | 4044211048327 |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 3.5 g |
| Weight per piece (including packaging) | 3.51 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |
| Product description | External insulated cross-connector |
| Colour | Yellow |

Technical data

Dimensions

| | |
|-------|---------|
| Width | 50.1 mm |
|-------|---------|

| | |
|------------|------|
| Pitch size | 5 mm |
|------------|------|

Ratings

| | |
|---------------|------|
| Rated current | 27 A |
|---------------|------|

| | |
|----------------------|---|
| Contamination degree | 3 |
|----------------------|---|

Connection data

| | |
|--------------|----|
| No. of poles | 10 |
|--------------|----|

Materials

| | |
|----------|--------|
| Material | Copper |
|----------|--------|

| | |
|---------|------------|
| Surface | Tin-plated |
|---------|------------|

| | |
|--------------------|---------------|
| Insulation housing | Polyamide 6.6 |
|--------------------|---------------|

| | |
|--------------------------|-----|
| Flammability class UL 94 | V-2 |
|--------------------------|-----|

| | |
|---------------------------|--------|
| Working temperature, min. | -40 °C |
|---------------------------|--------|

| | |
|---------------------------|--------|
| Working temperature, max. | 105 °C |
|---------------------------|--------|

Further technical data

| | |
|---------------|---------|
| Mounting type | Plug in |
|---------------|---------|

| | |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

| | |
|-------------------------------|---|
| Touch protection is available | ✓ |
|-------------------------------|---|

| | |
|-----------------------------|----|
| Number of bridged terminals | 10 |
|-----------------------------|----|

Environmental Product Compliance

| | |
|---------------|-----|
| REACH Conform | yes |
|---------------|-----|

| | |
|----------------------|------------|
| REACH Reference date | 2023-01-17 |
|----------------------|------------|


| | |
|--------------------------------|----|
| REACH Candidate Substance Note | No |
|--------------------------------|----|

| | |
|--------------|-----|
| RoHS Conform | yes |
|--------------|-----|

Media


Accessories

##INVERSE##CONTA-CONNECT




Double-level terminal/block variant, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------|---------------|----------------|
| <u>1208.2</u> | KBLD 2,5 m.B. BG | 4044211028374 | 10 ST |




Feed-through terminal/block variant, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| <u>1298.2</u> | KBL 2,5 m.B. BG | 4044211040499 | 10 ST |




Feed-through terminal for direct mount/block variant, Screw connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Width: 5 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1387.2</u> | KBL 2,5-D BG | 4044211044282 | 100 |




Double-level terminal/block variant, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1207.2</u> | KBLD 2,5 BG | 4044211028282 | 10 ST |



Feed-through terminal/block variant, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 2.5 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1297.2</u> | KBL 2,5 BG | 4044211040383 | 10 ST |



Feed-through terminal for direct mount/block variant, Screw connection, Mounting type: Mounting surface, Rated cross-section: 2.5 mm², Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| <u>1384.2</u> | KBL 2,5/10-D BG | 4044211044251 | 10 |