



The security shield tool is permanently attached, 4/ 3/4" (120mm), and pivots in 90-degree increments.

These tools are ideal for hard to reach shielded F connectors F Connector fittings where a pre-set torque is required.

The **TWAFST-71622** is set at .22 in./lb (2.49 NM)

The **TWAFST-71630** is set at .30 in./lb (3.39 NM)

SPECIFICATIONS	TWAFST-71622	TWAFST-71630
<b>HEAD TYPE</b>	Swivel	Swivel
<b>SIZE</b>	7/16" (11.11mm) Shield	7/16" (11.11mm) Shield
<b>TORQUE</b>	22 inch-lbs (2.49 N-m)	30 inch-lbs (3.39 N-m)
<b>SECURITY SHIELD LENGTH</b>	4 3/4" (120 mm)	4 3/4" (120 mm)
<b>MATERIAL</b>	High Carbon Alloy Steel	High Carbon Alloy Steel
<b>FINISH</b>	Black Oxide	Black Oxide
<b>HANDLE</b>	Ergonomic Cushion Grip	Ergonomic Cushion Grip
<b>COLOR</b>	Red Handle	Red Handle
<b>WEIGHT</b>	0.724 lbs	0.724 lbs
<b>UPC NO.</b>	811490016644	811490016651

**MADE FOR LIFE®**