

## 1.5kW Single-Phase Local Metered PDU, 100-127V Outlets (13 5-15R), 5-15P Input with 6 ft. (1.83 m) Cord, 1U Rack-Mount

MODEL NUMBER: PDUMH15-6



### Highlights

- Local metered single phase 12A 100-127V PDU
- 1U horizontal rackmount, Digital current meter
- NEMA 5-15P input with 6ft / 1.8m line cord
- 13 NEMA 5-15R outlets (1 front / 12 rear)
- Reversible housing, 4.5 in / 11.4cm depth

### Package Includes

- PDUMH15-6 Local Metered rackmount PDU
- Owner's manual with warranty information

### Features

- 15A single phase 100-127V Local Metered Power Distribution Unit / PDU (Agency de-rated to 12A continuous)
- Built-in 2 digit visual meter continuously reports PDU load level in amps
- Attached NEMA 5-15P 15A 120V input plug with 6 ft. / 1.8m line cord
- 1U horizontal rackmount format installs in one rack space
- 13 NEMA 5-15R outlets (1 front facing / 12 rear)
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Optional PDUSIDEBRKT enables 0U vertical rackmount in compatible racks
- Back panel grounding lug

## Specifications

| OVERVIEW                       |                                   |
|--------------------------------|-----------------------------------|
| UPC Code                       | 037332182883                      |
| PDU Type                       | Local Metered                     |
| INPUT                          |                                   |
| Input Phase                    | Single-Phase                      |
| PDU Input Voltage              | 100; 120; 125; 127                |
| Recommended Electrical Service | Single-phase 15A 100-127V service |

|  |   |
|--|---|
| Maximum Input Amps                           | 12  |
| Maximum Input Amps Details                   | Agency de-rated to 12A continuous   |
| PDU Plug Type                                | NEMA 5-15P  |
| Input Cord Length (ft.)                      | 6   |
| Input Cord Length (m)                        | 1.83  |
| <b>OUTPUT</b>                                |   |
| Output Capacity Details                      | 1.52kW (127V), 1.44kW (120V), 1.2kW (100V) / 12A total capacity; 12A max per outlet |
| Frequency Compatibility                      | 50 / 60 Hz  |
| Output Receptacles                           | (13) 5-15R  |
| Output Nominal Voltage                       | 100-127V  |
| Overload Protection                          | 15A circuit breaker   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Front Panel LCD Display                      | Digital display reports total PDU output current in amps                            |
| <b>SURGE / NOISE SUPPRESSION</b>             |   |
| Automatic Shut-Off                           | No  |
| <b>PHYSICAL</b>                              |   |
| Material of Construction                     | Metal   |
| Form Factors Supported                       | 1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation     |
| Minimum Required Rack Depth (cm)             | 19.05   |
| Minimum Required Rack Depth (inches)         | 7.5   |
| Outlets Measurement (Center to Center)       | Rear Side = 30.20mm   |
| PDU Form Factor                              | Horizontal (1U)   |
| Shipping Dimensions (hwd / in.)              | 2.40 x 9.30 x 20.60   |
| Shipping Dimensions (hwd / cm)               | 6.10 x 23.62 x 52.32  |
| Shipping Weight (lbs.)                       | 4.30  |
| Shipping Weight (kg)                         | 1.95  |
| Unit Dimensions (hwd / in.)                  | 1.750 x 17.300 x 3.750  |
| Unit Dimensions (hwd / cm)                   | 4.45 x 44.45 x 11.43  |
| Unit Weight (lbs.)                           | 4.5   |
| Unit Weight (kg)                             | 2.04  |
| <b>ENVIRONMENTAL</b>                         |   |

# TRIPP-LITE

by **EATON**

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

|                                      |  |
|--------------------------------------|--|
| Operating Temperature Range          | 32° to 104°F (0° to 40°C)                  |
| Storage Temperature Range            | -22° to 122°F (-30° to 50°C)               |
| Relative Humidity                    | 5% to 95% non-condensing                   |
| Operating Elevation (ft.)            | 0-10,000                                   |
| Operating Elevation (m)              | 0-3000                                     |
| <b>FEATURES &amp; SPECIFICATIONS</b> |  |
| Grounding                            | Rear grounding lug                         |
| <b>STANDARDS &amp; COMPLIANCE</b>    |  |
| Product Certifications               | RETIE (Colombia); NOM (Mexico); UL 60950-1 |
| Product Compliance                   | RoHS                                       |
| <b>WARRANTY &amp; SUPPORT</b>        |  |
| Product Warranty Period (Worldwide)  | 2-year limited warranty                    |

# TRIPP-LITE

by **EATON**

© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.