SIEMENS

Data sheet

6GK5992-4SA00-8AA0

product type designation

MM992-4CU

SCALANCE X accessory; Media module MM992-4CU; 4x 1000 Mbit/s RJ45 ports, electrical; without retaining collar



interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	4
number of electrical connections	
 for network components or terminal equipment / maximum 	4
number of 10/100/1000 Mbit/s RJ45 ports	4
type of electrical connection	
 for network components or terminal equipment 	RJ45
ambient conditions	
ambient temperature	
during operation	0 60 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	Media module
width	120.3 mm
height	22.3 mm
depth	275.5 mm
net weight	0.3 kg
fastening method	latched
 installation in media module slot 	Yes
standards, specifications, approvals	
standard	
 for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-7
 for emitted interference 	EN 61000-6-4 (Class A)
for interference immunity	EN 61000-6-2
certificate of suitability	EN 61000-6-2:2005, EN 61000-6-4:2007
CE marking	Yes
C-Tick	Yes
 KC approval 	Yes
● E1 approval	No
Marine classification association	
 French marine classification society (BV) 	Yes

further information / internet-Links

Internet-Link

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx-Download-Manager

• to website: Industry Online Support

http://www.siemens.com/simatic-net

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

last modified:

12/15/2020 🖸