

Specification Sheet

Part Number: 596-00826

Pre-Printed Vinyl Solar Labels are made with UV-stable inks and

materials for durability and weather resistance.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC® & IFC standards for printed text, character height, color and

outdoor UV stability to pass inspections.

ADVERTENCIA:

CONEXIÓN DE SALIDA DEL INVERSOR.

NO REUBICAR ESTE DISPOSITIVO DE SOBRECARGA.

Pre-printed labels offer significant time and cost savings over high-priced plastic engraved phenolic placards and the lead time of purchased markers.

Solar Label, Spanish, WARNING INVERTER OUTPUT...OVERCURRENT DEVICE, 4.12" x .75", VL, Orange,50/roll

Article Number 596-00826

Type IOCODS

Color Orange (OG)

Quantity Per roll

D 1 4	D : 4:
Product	Description
1 TOUGUL	Description

HellermannTyton pre-printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, Spanish, WARNING INVERTER OUTPUT...OVERCURRENT DEVICE, 4.12" x .75", VL,

Orange,50/roll

Global Part Name

IOCODS-443/281-OG

Local Order Number 2

English Version: 596-00589

Width W (Imperial)

4.125

Width W (Metric)

104.6

Thickness T (Imperial)

0.0025

Thickness T (Metric)

64.0

Height H (Imperial)

0.75

Height H (Metric)

19.05

Material

Type 443/281, UV-stabilised, flexible white vinyl with clear polyester laminate (443/281)

Material Shortcut 443/281 Adhesive Acrylic Halogen Free No UV Resistant (Yes/No) Yes Adhesive Operating Temperature -40°F to +174°F (-40°C to +79°C) -40°F to +174°F (-40°C to +79°C) **Operating Temperature** Reach Compliant (Article 33) Yes **ROHS Compliant** Yes Certification/Specification UL 969 NEC2014 UL Recognized (US) Yes 50 Package Quantity (Imperial) Package Quantity (Metric) 50 **Customs Number** 3919102055 Labels per Column 1

1

Labels per Row

© 2023 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions