

28157.7 PVC-PTS 60X62 WH

Device and installation marker, Length: 62 mm, Width: 60 mm, Colour: White

RAL: 9010

Business data

Article number	28157.7
Article name	PVC-PTS 60X62 WH
GTIN (EAN)	4044211213039
Packaging unit	100
Quantity unit	PC
Number of markers per card	4 ST
Weight per piece (not including packaging)	2.7 g
Weight per piece (including packaging)	2.7 g
Unit of weight	G
Customs number	39204910
Country of origin	IT
Prio-Article	28157.7
Product description	Device and installation marker

28157.7 PVC-PTS 60X62 WH

Technical data

Dimensions

Length	62 mm
Width	60 mm
Hole diameter	31 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Mounting	Unter Bedienelement
Software code	1003

Environmental Product Compliance

REACH Conform	yes
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

28157.7 PVC-PTS 60X62 WH

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST
