

Data sheet

3635.2 ZS/H0/ZTR



Fuse plug, Colour: Yellow

RAL: 1026

Business data

Article number	3635.2
Article name	ZS/H0/ZTR
GTIN (EAN)	4044211059996
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	6.34 g
Weight per piece (including packaging)	6.55 g
Unit of weight	G
Customs number	85369010
Country of origin	DE
Product description	Fuse plug
Colour	Yellow

Technical data

Ratings

Rated voltage (determined by the illuminated display and fuse being used)	400 V
Rated impulse voltage	4 kV
Overvoltage category	III
Contamination degree	3

Connection data

Connection principle	Plug in
----------------------	---------

Materials

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C

Further technical data

Fuse size	5 x 20 mm
Power loss in singular arrangement - overload and short-circuit protection, max.	2,5 / 6,4 W / A
Power loss in compound arrangement - overload and short-circuit protection, max.	1,6 / 6,4 W / A
Power loss in singular arrangement - only short-circuit protection, max.	5 / 6,3 W / A
Power loss in compound arrangement - only short-circuit protection, max.	2,5 / 6,4 W / A
Version of fuse cartridge	G fuse 5 x 20

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-01-17
REACH Candidate Substance Note	No
RoHS Conform	yes

Approvals

CSA approval

CSA approval	C22.2 No 158
CSA approval granted	yes
CSA Usegroup B: rated voltage	300 V
CSA Usegroup B: rated current	10 A
CSA Usegroup C: rated voltage	300 V
CSA Usegroup C: rated current	10 A

CSAus approval


CSAus approval	UL 1059
CSAus approval granted	yes
CSAus Usegroup B: rated voltage	300 V
CSAus Usegroup B: rated current	10 A
CSAus Usegroup C: rated voltage	300 V
CSAus Usegroup C: rated current	10 A

Media




Accessories

##INVERSE##CONTA-CONNECT




Fuse-disconnect terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3268.2</u>	FTRK 2,5/3A/ZS BG	4044211138011	100




Fuse-disconnect terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3263.2</u>	FTRK 2,5/2A/ZS BG	4044211137847	100



Fuse-disconnect terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3263.2</u>	FTRK 2,5/2A/ZS BG	4044211137847	100



Basic terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3258.2</u>	FTRK 2,5/3A/OT BG	4044211137717	100



Fuse-disconnect terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3616.2</u>	ZTRK 2,5/2A/ZS BG	4044211059804	100



Fuse-disconnect terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3621.2</u>	ZTRK 2,5/3A/ZS BG	4044211059859	100

Data sheet

3635.2 ZS/H0/ZTR

##INVERSE##CONTA-CONNECT



Fuse-disconnect terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3626.2</u>	ZTRK 2,5/4A/ZS BG	4044211059903	100



Basic terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3611.2</u>	ZTRK 2,5/4A/OT BG	4044211059750	100



Basic terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3609.2</u>	ZTRK 2,5/2A/OT BG	4044211059736	100



Basic terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm², Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3610.2</u>	ZTRK 2,5/3A/OT BG	4044211059743	100