TRIPP-LITE by Fit-N

2U UPS Replacement 72VDC Battery Cartridge for select Tripp Lite SmartOnline UPS

MODEL NUMBER: RBC96-2U



Description

Tripp Lite's premium UPS replacement battery cartridges breathe new life into UPS systems suffering from expired or weak internal batteries. Each replacement battery cartridge is carefully screened and certified to meet or exceed original specifications, and ships ready for installation into your UPS system. Reusable packaging holds expired batteries for recycling center delivery. See Tripp Lite's UPS replacement battery web page to confirm compatibility and quantity required. COMPATIBLE WITH TRIPP LITE MODELS SU3000RTXL2U and SUINT3000RTXL2U

Features

- Restores UPS runtime performance to original specifications
- · Comes pre-assembled and ready for installation
- Reusable packaging holds expired batteries for recycling center delivery

Specifications

OVERVIEW	
UPC Code	037332146403
BATTERY	
DC System Voltage (VDC)	72
Included Battery Set	Contains (6) 12V 9AH sealed lead acid batteries
Typical Battery Lifespan	3 to 5 years, depending on UPS operating conditions
PHYSICAL	
Minimum Required Rack Depth (cm)	22.86

Highlights

- Tripp Lite-certified premium battery cartridge
- Pre-assembled and wired battery kit offers simple installation
- Rugged leak-proof construction
- Maintenance free
- Wide operating temperature range

Package Includes

 One pre-assembled 72V battery kit (consists of two strings of 12V batteries)

TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

Minimum Required Rack Depth (inches)	9	
Shipping Dimensions (hwd / in.)	6.37 x 20.10 x 7.48	
Shipping Dimensions (hwd / cm)	16.18 x 51.05 x 19.00	
Shipping Weight (lbs.)	41.00	
Shipping Weight (kg)	18.60	
Unit Dimensions (hwd / in.)	4.140 x 17.900 x 5.280	
Unit Dimensions (hwd / cm)	10.4 x 13.5 x 45.5	
Unit Weight (lbs.)	39.0	
Unit Weight (kg)	17.69	
ENVIRONMENTAL		
Relative Humidity	0-95% non-condensing	
Operating Elevation (ft.)	10,000 ft.	
Storage Elevation (ft.)	10,000 ft.	
Operating Elevation (m)	3,000 m	
Storage Elevation (m)	3000 m	
WARRANTY & SUPPORT		
Product Warranty Period (U.S. & Canada)	18-month limited warranty	
Product Warranty Period (International)	1-year limited warranty	
Product Warranty Period (Mexico)	1-year limited warranty	
Product Warranty Period (Puerto Rico)	1-year limited warranty	



© 2022 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.