




MUS51-25-25-SS

Ruland MUS51-25-25-SS, 25mm x 25mm Single Universal Joint, Friction Bearing, Stainless Steel, 50.7mm OD, 139.7mm Length





Description

Ruland MUS51-25-SS is a single cardan friction bearing universal joint with 25mm x 25mm bores, 50.7mm OD, and 139.7mm length. It is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. MUS51-25-25-SS is made from high grade stainless steel for corrosion resistance. It can be combined with boot UBOOT32/51-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

Prop 65	▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov .		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Tariff Code	8483.60.4000	UNSPC	25173810
Recommended Lubricant	LUBRIPLATE No. 1200-2	UPC	634529287811
Country of Origin	USA	Weight (lbs)	3.289000
Material Specification	Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainless Steel	Manufacturer	Belden Universal
Rated Torque	352.5 Nm	Max Operating Angle	45°
Hub Depth (LH)	43.2 mm	Peak Torque	1186.3 Nm
Length (L)	139.7 mm	Yoke Length (LY)	69.9 mm
Joint Outer Diameter (OD)	50.7 mm	Bore Tolerance	+0.021 mm / -0.000 mm
B1 Max Shaft Penetration	43.2 mm	B2 Max Shaft Penetration	43.2 mm
Bore (B1)	25 mm	Small Bore (B2)	25 mm