



Screw Terminal Blocks

230 K/ 3 DS

terminal block, 3 pole, insulating material: PA, cross-section rating: 2.5 mm², pin spacing: 8.00 mm, mounting hole diameter: 2.8 mm, wire protector (DS): yes, fixing: screw, voltage rating: 450 V, current rating: 24 A



Order Info

| | |
|----------------------------|---------------|
| reference number (ref.no.) | 121703 |
| PU | 1,500 |
| EAN | 4028012105373 |

Type

| | |
|-------------------------|---------------------|
| type | terminal block |
| number of poles | 3 pole |
| clamping units per pole | 1 |
| colour | natural |
| cross-section rating | 2.5 mm ² |
| connection type | screw |
| wire protector (DS) | yes |

Technical Data

| | |
|------------------------------------|---------------------|
| voltage rating | 450 V |
| current rating | 24 A |
| insulating material | PA |
| contact material | brass |
| core cross-section min. | 0.5 mm ² |
| core cross-section max. | 2.5 mm ² |
| flammability rating | V-2 |
| min. ambient temperature | -40 °C |
| max. ambient temperature operation | 85 °C |
| type of conductor solid | yes |
| type of conductor flexible | yes |
| type of conductor stranded | yes |
| stripping length | 5.0-5.5 mm |
| assembly contact screw | 0,8x4,0 / ⚙ 0,5 Nm |
| mounting hole diameter | 2.8 mm |
| pin spacing | 8.00 mm |
| fixing | screw |

Approvals

| | |
|-------------------------|------------------------------|
| acc. to EN 60998 | Download PDF |
| acc. to UL | Download PDF |
| acc. to CSA | Download PDF |

Accessories

| | |
|------------------|--------|
| 230 BZ/ 3 | 191203 |
| ZEL 110 | 196420 |