



Figure similar

Electrically held lighting contactor, Contactor amp rating 30A, 0 N.C. / 3 N.O. Poles, 110VAC 50HZ/120VAC 60HZ coil, Non-combination type, (no disconnect device), Encl NEMA type 4X 304 S-Steel, Water/dust tight noncorrosive

|  |  |
|--|--|
| product brand name   | Class LE   |
| design of the product  | Electrically held lighting contactor   |
| special product feature  | Compact design; Finger safe control terminals  |
| <b>General technical data</b>  |  |
| weight [lb]  | 19 lb  |
| Height x Width x Depth [in]  | 16 × 13 × 6 in   |
| touch protection against electrical shock  | NA for enclosed products   |
| installation altitude [ft] at height above sea level maximum   | 6560 ft  |
| ambient temperature [°F]   |  |
| <ul style="list-style-type: none"> <li>during storage</li> <li>during operation</li> </ul>   | -67 ... +176 °F<br>32 ... 104 °F   |
| ambient temperature  |  |
| <ul style="list-style-type: none"> <li>during storage</li> <li>during operation</li> </ul>   | -55 ... +80 °C<br>0 ... 40 °C  |
| country of origin  | USA  |
| <b>Contactors</b>  |  |
| size of contactor  | 30 Amp   |
| number of NO contacts for main contacts  | 3  |
| number of NC contacts for main contacts  | 0  |
| operating voltage for main current circuit at AC at 60 Hz maximum  | 600 V  |
| mechanical service life (switching cycles) of the main contacts typical  | 10000000   |
| contact rating of the main contacts of lighting contactor  |  |
| <ul style="list-style-type: none"> <li>at tungsten (1 pole per 1 phase) rated value</li> <li>at tungsten (2 poles per 1 phase) rated value</li> <li>at tungsten (3 poles per 3 phases) rated value</li> <li>at ballast (1 pole per 1 phase) rated value</li> <li>at ballast (2 poles per 1 phase) rated value</li> <li>at ballast (3 poles per 3 phases) rated value</li> <li>at resistive load (1 pole per 1 phase) rated value</li> <li>at resistive load (2 poles per 1 phase) rated value</li> <li>at resistive load (3 poles per 3 phases) rated value</li> </ul> | 30A @277V 1p 1ph<br>30A @480V 2p 1ph<br>30A @480V 3p 3ph<br>30A @347V 1p 1ph<br>30A @600V 2p 1ph<br>30A @600V 3p 3ph<br>30A @600V 1p 1ph<br>30A @600V 2p 1ph<br>30A @600V 3p 3ph |
| <b>Auxiliary contact</b>   |  |
| number of NC contacts at contactor for auxiliary contacts  | 1  |
| number of NO contacts at contactor for auxiliary contacts  | 1  |
| number of total auxiliary contacts maximum   | 4  |
| contact rating of auxiliary contacts of contactor according to UL  | A600 / Q600  |

| Coil  |  |
|---|--|
| type of voltage of the control supply voltage   | AC   |
| control supply voltage  |  |
| • at AC at 50 Hz rated value  | 110 V  |
| • at AC at 60 Hz rated value  | 120 V  |
| apparent pick-up power of magnet coil at AC   | 87 VA  |
| apparent holding power of magnet coil at AC   | 9.4 VA   |
| operating range factor control supply voltage rated value of magnet coil  | 0.85 ... 1.1                                   |
| Enclosure   |  |
| degree of protection NEMA rating of the enclosure   | NEMA 4x 304 stainless steel enclosure          |
| design of the housing   | dustproof, waterproof & resistant to corrosion |
| Mounting/wiring   |  |
| mounting position   | Vertical                                       |
| fastening method  | Surface mounting and installation              |
| type of electrical connection for supply voltage line-side  | Screw-type terminals                           |
| tightening torque [lbf-in] for supply   | 18 ... 22 lbf-in                               |
| type of connectable conductor cross-sections at line-side at AWG cables single or multi-stranded                        | 2x (16 ... 12 AWG), 2x (14 ... 8 AWG)          |
| temperature of the conductor for supply maximum permissible   | 75 °C  |
| material of the conductor for supply  | CU   |
| type of electrical connection for load-side outgoing feeder   | Screw-type terminals                           |
| tightening torque [lbf-in] for load-side outgoing feeder  | 18 ... 22 lbf-in                               |
| type of connectable conductor cross-sections at AWG cables for load-side outgoing feeder single or multi-stranded       | 2x (16 ... 12 AWG), 2x (14 ... 8 AWG)          |
| temperature of the conductor for load-side outgoing feeder maximum permissible  | 75 °C  |
| material of the conductor for load-side outgoing feeder   | CU   |
| type of electrical connection of magnet coil  | Screw-type terminals                           |
| tightening torque [lbf-in] at magnet coil   | 7 ... 10 lbf-in                                |
| type of connectable conductor cross-sections of magnet coil at AWG cables single or multi-stranded                      | 2x (20 ... 16 AWG), 2x (18 ... 14 AWG)         |
| temperature of the conductor at magnet coil maximum permissible   | 75 °C  |
| material of the conductor at magnet coil  | CU   |
| type of electrical connection at contactor for auxiliary contacts   | Screw-type terminals                           |
| tightening torque [lbf-in] at contactor for auxiliary contacts  | 7 ... 12 lbf-in                                |
| type of connectable conductor cross-sections at contactor at AWG cables for auxiliary contacts single or multi-stranded | 2x (20 ... 16 AWG), 2x (18 ... 14 AWG)         |
| temperature of the conductor at contactor for auxiliary contacts maximum permissible                                    | 75 °C  |
| material of the conductor at contactor for auxiliary contacts   | CU   |
| Short-circuit current rating  |  |
| design of the fuse link for short-circuit protection of the main circuit required                                       | 100kA@600V (Class J 40A max)                   |
| design of the short-circuit trip  | Thermal magnetic circuit breaker               |
| breaking capacity maximum short-circuit current (I <sub>cu</sub> )  |  |
| • at 240 V  | 24 kA  |
| • at 480 V  | 65 kA  |
| • at 600 V  | 14 kA  |
| certificate of suitability  | NEMA ICS 2; UL 508                             |

#### Further information

**Industrial Controls - Product Overview (Catalogs, Brochures,...)**

[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:LEN04C003120B>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/US/en/ps/US2:LEN04C003120B>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:LEN04C003120B&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:LEN04C003120B&lang=en)

**Certificates/approvals**

<https://support.industry.siemens.com/cs/US/en/ps/US2:LEN04C003120B/certificate>

**last modified:**

1/25/2022 