



RECOMMENDED LAYOUT
FOR .125 THICK P.C. BOARD

1. MATES WITH HOUSING 480285.
2. PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-3

1 MATES WITH HOUSING 480285.
2 PARTS COMPLY WITH AMP SOLDERABILITY SPEC 109-11-3.
3 DIMENSION SHOWN REPRESENT PRODUCT IN DRY CONDITION. ADDITIONAL 2% GROWTH DUE TO END USE LOCATION MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

ASSEMBLY NO.	HSG. MATL & COLOR	PIN MATL & FINISH
350219-1	NYLON - NATURAL	copper alloy · PRE-TIN

Unpublished copy not to be reproduced nor published without written permission of AMP Incorporated

©1973 BY AMP INCORPORATED. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.

CUSTOMER COPY
REFERENCE ONLY

DR 9. Eckman 6-13-73	MATERIAL AND FINISH: SEE TABLE
CHK E. Graver 6-14-73	CLASS: H
DE	WIRE – RANGE – INSULATION: H – H
APP Emf. P. Kerwin 6/14/73	TOLERANCE EXCEPT AS NOTED ±.015 ±1° 0'; SCALE: H; LOC CM; B; NO 350219; REV M1
	NAME 10 CIRCUIT MATE-N-LOK P.C. BOARD HEADER

TE Connectivity

LTR	REVISION RECORD	DR	CHK	DATE
K	RESTORED	BKD	RS	3/28/85
K	REV. PER M-7375	SS	CM	8-27-84
J	2.50" TOOLING HOLE REF M-7285	DAS	DH	4/11/83
H	ADDED NOTE 3, M-6694	MSF	DH	4-30-81
G	REV. TAIL LENGTH M-5334	MSF	DH	3-24-77
F	REVISED M-4161	MF	DH	3-7-77
E	ECN M-3871	RRN	DH	5-10-76
D	ECN M-3452	GV	RRF	5/18/76
C	ECN M-3158	BC	MW	9/4/75
B	SUPERSEDED BY 350219 ADDED COLOR			6/2/75

LTR	REVISION RECORD	PJ	VS	DATE
M1	REVISED PER ECR-21-117185			20OCT2021
M	OBSOLETE -2 PER ECN CM-2709	MG	RS	6-26-82
L	OBSOLETE 1-1, 1-2, 2-1, 2-2, 3-1, 3-2, 4-1, 4-2, 5-1, 5-2, 6-1, 6-2, 7-1, 7-2, 8-1, 8-2, 9-1, 9-2 CM 4/13	KW RS		4-19-86

REQUIRED PER ASSEMBLY

DESCRIPTION

NUMBER 350219

PRINT 53

DIMENSIONS IN INCHES. DO NOT SCALE PRINT.

AMP 1253 REV 11/65

7 6 5 4 3 2 1