


- [Circuit Board Indicators](#)
- [Panel Mount Indicators](#)
- [Solid State Lighting](#)
- [Traffic Signals](#)
- [Vehicle Lighting](#)
- [Rail](#)
- [Obstruction Lighting](#)
- [Hazardous Area Lighting](#)
- [Heliport Lighting](#)

**Circuit Board Indicators - Through Hole Indicators**

|                      |                         |
|----------------------|-------------------------|
| <b>P/N# 5532203F</b> | <b>3 mm Lens</b>        |
| Description          | 3 mm Bi-Level CBI       |
| Package Options      | 50 Pieces Per Bag       |
| Product Type         | Through Hole Indicators |
| Sub Product Type     | with Bi-Level Housing   |
| Configuration        | 3 mm Lens               |
| Viewing              | Right Angle             |
| Viewing Angle        | 45                      |
| Test Current (mA)    | 10mA                    |

**Absolute Maximum Ratings (Ta = 25 °)**

|                |                        |
|----------------|------------------------|
| Solder Temp    | <b>260Å° for 5 sec</b> |
| Operating Temp | <b>-55 to +100° C</b>  |
| Storage Temp   | <b>-55 to +100° C</b>  |



**Distributor Stock Check**

Check stock with our distributors now.

5532203F

[check stock](#)

- [how to purchase](#)
- [sales contacts](#)
- [stock check](#)

**search**

[Product Line Search](#)

Please select a Product Line to search.

[find](#)

**Part # / Text Search**

Part No.:

Text Search:

[search](#)

[quick links](#)

**Dialight Corporate Video**

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

**Application Notes**  
[FAQs](#)

**Dialight Ltd (UK)**  
**Dialight Garufo**  
**Dialight BLP**  
**LumiDrives**

**Operating Characteristics**

|                            | Found in position(s): 1 | Found in position(s): 2 |
|----------------------------|-------------------------|-------------------------|
| LED Position               |                         |                         |
| Color                      | Blank                   | Yellow                  |
| Lamp Type                  | Single Color            | Single Color            |
| LED Type                   |                         | High Efficiency         |
| Intensity Min (mcd)        |                         | 10.0                    |
| Intensity Typ (mcd)        |                         |                         |
| Intensity Max (mcd)        |                         | 50                      |
| Fwd Voltage Min            |                         |                         |
| Fwd Voltage Typ            |                         |                         |
| Fwd Voltage Max            |                         |                         |
| Dom Wavelength Min (nm)    |                         |                         |
| Dom Wavelength Typ (nm)    |                         |                         |
| Dom Wavelength Max (nm)    |                         |                         |
| Power Dissipation Max (mW) |                         |                         |
| Backlighting               |                         |                         |
| Pitch Between Vertical     |                         |                         |
| Pitch Between Horizontal   |                         |                         |
| Lum Intensity Min          |                         |                         |
| Lum Intensity Typ          |                         |                         |
| Lum Intensity Max          |                         |                         |

menu rendered