

Data sheet | Item number: 706-2300/402-300

System cable; for Siemens S7-300; 8 analog inputs (current); Length: 3 m;

Conductor cross-section: 0.25 mm²

www.wago.com/706-2300/402-300



Data Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 1 A.
------	---

Electrical data

Inputs/outputs	8 analog inputs; current
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data

Compatible PLC Modules	Siemens S7-300
Compatible PLC I/O Card Types	6ES7 331-1KF02-0AB0
Connection type (1)	System
Pole number 1	25
Pluggable connectors	D-sub female connector
Connection type 2	System
Pole number 2	40
Connector 2	Siemens 6ES7-392-1BM00-0AA0
Cable type	LiYCY
Wire cross-section	0.25 mm ²
Color code	per DIN VDE 47100

Physical data

Cable length	3 m
--------------	-----

Material data

Weight	404 g
--------	-------

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Environmental requirements

Surrounding air temperature (operation) -20 ... 50 °C

Commercial data

PU (SPU)	1 Stück
Packaging type	box
GTIN	4045454979034
Customs tariff number	85444290900

Downloads

Documentation

System Description

WAGO System Wiring, Selection Guide This guide will help you select the appropriate interface modules and system cables for the controller you are usng.	pdf 545.9 kB	Download
---	-----------------	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-2300/402-300 System cable; for Siemens S7-300; 8 analog inputs (current); Length: 3 m; Conductor cross-section: 0.25 mm ²	URL	Download
--	-----	----------

Installation Notes

Subject to changes. Please also observe the further product documentation!